



OPEN ACCESS

APPROVED BY  
 Frontiers Editorial Office,  
 Frontiers Media SA, Switzerland

\*CORRESPONDENCE  
 Frontiers Production Office,  
 production.office@frontiersin.org

RECEIVED 18 August 2023  
 ACCEPTED 18 August 2023  
 PUBLISHED 03 November 2023

CITATION  
 Frontiers Production Office (2023),  
 Erratum: Global versus local Lyapunov  
 approach used in disturbance observer-  
 based wind turbine control.  
*Front. Control. Eng.* 4:1279811.  
 doi: 10.3389/fcteg.2023.1279811

COPYRIGHT  
 © 2023 Frontiers Production Office. This  
 is an open-access article distributed  
 under the terms of the [Creative  
 Commons Attribution License \(CC BY\)](#).  
 The use, distribution or reproduction in  
 other forums is permitted, provided the  
 original author(s) and the copyright  
 owner(s) are credited and that the original  
 publication in this journal is cited, in  
 accordance with accepted academic  
 practice. No use, distribution or  
 reproduction is permitted which does not  
 comply with these terms.

# Erratum: Global versus local Lyapunov approach used in disturbance observer-based wind turbine control

Frontiers Production Office\*

Frontiers Media SA, Lausanne, Switzerland

KEYWORDS

global and local Lyapunov approach, Takagi–Sugeno framework, model-based controller and observer design, feedforward-feedback control, linear-matrix-inequality and pole region-based controller design, wind turbine application, elaborated wind turbine simulation model, load analysis

## An Erratum on Global versus local Lyapunov approach used in disturbance observer-based wind turbine control

by Gautérin E, Pöschke F and Schulte H (2023). *Front. Control. Eng.* 3:787530. doi: 10.3389/fcteg.2022.787530

Due to a production error, the equation in section 2.2.1 **Global Controller** was incorrect.

The incorrect equation was:  $X = P^{-1} \left( \Rightarrow \stackrel{10}{=} X \right)$

The correct equation is:  $X = P^{-1} \left( \Rightarrow \stackrel{Eq. 10}{=} X \right)$

In section 3.2 **Simulation Results: Disturbance Observer Variation, Resulting System Dynamics and Mechanical Loads**, at the beginning of subsection **Pole locations**, Figure 5 instead of **Figure 4** was incorrectly referenced.

Due to a production error, the equations in section **Discussion**, subsection **Pole Locations** were incorrect.

The incorrect equations were  $s_{p,i}^{OL,3}$  and  $s_{p,i}^{OL,1/2}$

The correct equations are  $s_{p,i}^{OL,1}$  and  $s_{p,i}^{OL,2 \vee 3}$

Due to a production error, the equation in section **Error-feedback gains** (page 16) was incorrect.

The incorrect equation was:  $\left| L_{iB}^{w,j} \right|_2 (\forall w \in [B, D]) > \left| L_{iB}^{w,j} \right|_2 (\forall w \in [G, I])$

The correct equation is:  $\| L_{iB}^{B,j} \|_2 > \| L_{iB}^{G,j} \|_2, \| L_{iB}^{C,j} \|_2 > \| L_{iB}^{H,j} \|_2$  and  $\| L_{iB}^{D,j} \|_2 > \| L_{iB}^{I,j} \|_2$

Due a production error, the first paragraph in section **Wind speed reconstruction and actuation** signals was incorrect. You can find the correct paragraph below:

With the mitigated error-feedback gains  $L_{iB}^{w,j}$ , the reconstructed states  $\hat{x}$ , especially the reconstructed wind speeds  $\hat{v}$ , are mitigated, too (see **Eq. 7<sup>11</sup>**): While the reconstructed wind speed

$\hat{v}^w(t_1)$  of a single and arbitrary time point  $t = t_1$  decreases *steadily* for the wind speed observer design with a local Lyapunov approach (i.e.,  $\hat{v}^F(t_1) \approx \hat{v}^G(t_1) > \hat{v}^H(t_1) > \hat{v}^J(t_1) > \hat{v}^I(t_1)$ )<sup>10</sup>, see left column in **Figure 6**, the reconstructed wind speed  $\hat{v}^w(t_1)$  for the wind speed observer design with a global Lyapunov approach decreases *unsteadily* (i.e.,  $\hat{v}^A(t_1) > \hat{v}^D(t_1) > \hat{v}^E(t_1) > \hat{v}^C(t_1) > \hat{v}^B(t_1)$ ), corresponding to the unsteady decrease of the mean Euclidean norm of the wind error state gains  $\|L_{iB}^{w,3}\|_2$  of the global wind speed observers (with  $w \in [A, E]$ , see **Table 3**; i.e.,  $\|L_{iB}^{A,3}\|_2 > \|L_{iB}^{D,3}\|_2 > \|L_{iB}^{C,3}\|_2 > \|L_{iB}^{B,3}\|_2$ )<sup>10</sup>

In the same section, **footnotes 12 and 13** were assigned incorrectly, and these have been replaced with **footnote 10** in the updated article.

<sup>10</sup>The global and local wind speed observers  $E$  and  $J$  are not taken into account, because of their (closed-loop) pole locations, which are moved beyond the open-loop pole locations, as explained before in the subsection Pole locations.

**Footnote 12** was also incorrect, the correct version is:

<sup>12</sup>with two exceptions for the tower *side-to-side*-bending moments  $S_{eq}^B(TwrBsMxt) < S_{eq}^J(TwrBsMxt)$  and  $S_{eq}^C(TwrBsMxt) < S_{eq}^I(TwrBsMxt)$  (see **Figure 8B** and line 7 in **Table A9** as well as line 7 in **Table A10**).

Due to a production error, section **Load Mitigation**, paragraph number 3, appears to be interrupted and broken into two parts. This has been corrected into one single paragraph.

In the Appendix, part of section **Specification of the LMI constraints** was not included in the article. The corrected entire section appears below:

To calculate the *mean* Euclidian norm  $\|L_{iB}^{w,j}\|_2$  of the error-feedback gains  $L_{iB}^{w,j}$  [see (26)] and the *average, mean* Euclidian norm  $\|L_{iB}^{w,j}\|_2$  [see (27)] the worksheet *Uebersicht\_L\_Matrizen\_Pitchwinkel-YYYY\_MM\_DD.xlsx* is used.

In the Appendix, the section **Load Analysis** was not included in the article. This has now been added to the article, you can find it below:

## Load analysis

For the ultimate loads  $\max^w$  and fatigue loads  $S_{eq}^w$  resulting from five different wind speed observers (i.e., for the  $w \in [A, E]$  **global wind speed observers** and  $w \in [A, E]$  **local wind speed observers**; see **Figure 8**), the steady increase or decrease of the loads is evaluated separately for each of the two observer approaches (see **Table A9**) and in comparison to each other (see **Table A10**).

Due to a production error, **Tables A9 and A10** in the Appendix were not included in the article, and the layout of **Tables A1–A8** in the Appendix was incorrect. The corrected Tables are listed below:

The font color has been corrected in the table captions and in the body of the text, throughout the article.

The publisher apologizes for this mistake. The original version of this article has been updated.

**TABLE A1** States of the  $i$  steady state operations points  $OP_i$  of the NREL FAST 5MW reference wind turbine with the wind speed  $v_{c,i}$ , rotor rotational speed  $\omega_{R,c,i}$ , generator torque  $T_{G,c,i}$  and pitch angle  $\beta_{c,i}$ .

$i$	$v_{c,i}$	$\beta_{c,i}$	$T_{G,c,i}$	$\omega_{R,c,i}$
1	3	0	2.912	3.4
2	4	0	5.193	4.6
3	5	0	8.079	5.7
4	6	0	11.646	6.9
5	7	0	15.843	8.0
6	8	0	20.671	9.2
7	9	0	26.128	10.3
8	9.5	0	29.094	10.9
9	10	0	32.267	11.4
10	10.5	0	35.547	12.0
11	11	0	40.433	12.1
12	11.5	2.2	43.094	12.1
13	12	4.1	43.094	12.1
14	12.5	5.5	43.094	12.1
15	13	6.6	43.094	12.1
16	14	8.6	43.094	12.1
17	15	10.4	43.094	12.1
18	16	12.0	43.094	12.1
19	17	13.4	43.094	12.1
20	18	14.8	43.094	12.1
21	19	16.1	43.094	12.1
22	20	17.4	43.094	12.1
23	21	18.6	43.094	12.1
24	22	19.7	43.094	12.1
25	23	20.8	43.094	12.1
26	24	22.0	43.094	12.1
27	25	23.0	43.094	12.1

**TABLE A2** State matrices  $A_{iB}$  and augmented state matrices  $\tilde{A}_{iB}$  of the  $B$ blade model (for the submodels  $i \in [15,18]$ ).

$A_{15B}$	0 -21.82 -	1 -5.41 -	$\tilde{A}_{15B}$	0 -21.82 0	1 -5.41 0	0 9.58 -0.25
$A_{16B}$	0 -21.88 -	1 -5.36 -	$\tilde{A}_{16B}$	0 -21.88 0	1 -5.36 0	0 9.51 -0.25
$A_{17B}$	0 -21.92 -	1 -5.35 -	$\tilde{A}_{17B}$	0 -21.92 0	1 -5.35 0	0 9.48 -0.25
$A_{18B}$	0 -21.95 -	1 -5.30 -	$\tilde{A}_{18B}$	0 -21.95 0	1 -5.30 0	0 9.38 -0.25

**TABLE A3** Input matrices  $B_{iB}$  and augmented input matrices  $\tilde{B}_{iB}$  of the  $B$ blade model (for the submodels  $i \in [15,18]$ ).

$B_{15B}$	0 -563.53 -	0 0 -	$\tilde{B}_{15B}$	0 -563.53 0	0 0 0
$B_{16B}$	0 -589.16 -	0 0 -	$\tilde{B}_{16B}$	0 -589.16 0	0 0 0
$B_{17B}$	0 -606.41 -	0 0 -	$\tilde{B}_{17B}$	0 -606.41 0	0 0 0
$B_{18B}$	0 -628.21 -	0 0 -	$\tilde{B}_{18B}$	0 -628.21 0	0 0 0

**TABLE A4 Common output matrix  $C_B$  and augmented common output matrix  $\tilde{C}_B$  of the Blade model (for all submodels).**

$C_B$	1	0	$\tilde{C}_B$	1	0	0
-------	---	---	---------------	---	---	---

**TABLE A5 Steady states  $\underline{x}_{c,iB}$  and augmented steady states  $\tilde{\underline{x}}_{c,iB}$  of the Blade model (for the submodels  $i \in [15,18]$ ).**

$\underline{x}_{c,15B}$	3.61 0 -	$\tilde{\underline{x}}_{c,15B}$	3.61 0 13
$\underline{x}_{c,16B}$	3.15 0 -	$\tilde{\underline{x}}_{c,16B}$	3.15 0 14
$\underline{x}_{c,17B}$	2.73 0 -	$\tilde{\underline{x}}_{c,17B}$	2.73 0 15
$\underline{x}_{c,18B}$	2.44 0 -	$\tilde{\underline{x}}_{c,18B}$	2.44 0 16

**TABLE A6 Steady state pitch angle  $\beta_{c,i}$  and generator torque  $T_{G,i}$  (for the submodels  $i \in [15,18]$ ).**

$\beta_{c,15}$ $T_{G,15}$	6.6 43.094
$\beta_{c,16}$ $T_{G,16}$	8.6 43.094
$\beta_{c,17}$ $T_{G,17}$	10.4 43.094
$\beta_{c,18}$ $T_{G,18}$	12.0 43.094

**TABLE A7 State feedback matrices  $K_{iR}$  of the (rigid body) Rotation drive train model (for the submodels  $i \in [15,18]$ ).**

$K_{15R}$	-1.31 0
$K_{16R}$	-1.03 0
$K_{17R}$	-0.85 0
$K_{18R}$	-0.71 0

**TABLE A8 Error state feedback gain matrices  $L_{iB}^{w,j}$  of the blade model based wind speed observers  $B$  for:**  
 - global Lyapunov approach with  $w \in [A, E]$   
 - local Lyapunov approach with  $w \in [F, J]$   
 - submodels  $i \in [15, 18]$   
 - matrix elements  $j \in [1, 3]$ .

	A	B	C	D	E	F	G	H	I	J
$L_{15B}^{w,1}$	3.87	2.81	2.04	1.28	0.30	4.06	3.02	1.79	0.38	-1.35
$L_{15B}^{w,2}$	-13.31	-15.30	-9.80	-5.92	-4.22	-14.19	-12.90	-8.78	-5.23	-4.46
$L_{15B}^{w,3}$	2.56	0.88	1.21	1.43	1.31	2.27	1.90	1.61	1.11	0.39
$L_{16B}^{w,1}$	3.87	2.81	2.04	1.28	0.30	4.07	3.07	1.84	0.43	-1.30
$L_{16B}^{w,2}$	-13.44	-15.45	-9.95	-6.05	-4.28	-14.33	-13.14	-9.18	-5.57	-4.85
$L_{16B}^{w,3}$	2.56	0.88	1.20	1.43	1.31	2.26	1.91	1.61	1.12	0.40
$L_{17B}^{w,1}$	3.88	2.81	2.04	1.28	0.30	4.07	3.08	1.85	0.44	-1.29
$L_{17B}^{w,2}$	-13.49	-15.50	-10.01	-6.10	-4.31	-14.39	-13.22	-9.30	-5.68	-4.98
$L_{17B}^{w,3}$	2.56	0.88	1.20	1.43	1.31	2.26	1.92	1.61	1.12	0.40
$L_{18B}^{w,1}$	3.88	2.81	2.04	1.28	0.29	4.08	3.13	1.90	0.50	-1.23
$L_{18B}^{w,2}$	-13.60	-15.62	-10.13	-6.19	-4.33	-14.51	-13.43	-9.70	-6.00	-5.39
$L_{18B}^{w,3}$	2.56	0.88	1.20	1.43	1.31	2.26	1.93	1.61	1.13	0.40

**TABLE A9 Analysis of the ultimate loads  $\max^w$  and fatigue loads  $S_{eq}^w$  resulting from five different wind speed observers regarding the steady increase or decrease of the loads (evaluated separately for each of the two Lyapunov approaches with  $w \in [A, E]$  for the global wind speed observers and with  $w \in [F, J]$  for the local wind speed observers; based on the loads depicted in Figure 8).**

Loads	Global Lyapunov approach	Local Lyapunov approach
$TwrBsMyt$	$\max^A > \max^B > \max^C > \max^D > \max^E$	$\max^F > \max^G > \max^H > \max^I > \max^J$
$TwrBsMxt$	$\max^A > \max^B < \max^C < \max^D < \max^E$	$\max^F \approx \max^G > \max^H > \max^I > \max^J$
$RootMxb1$	$\max^A > \max^B < \max^C < \max^D < \max^E$	$\max^F > \max^G > \max^H > \max^I > \max^J$
$RootMyb1$	$\max^A < \max^B > \max^C > \max^D > \max^E$	$\max^F > \max^G < \max^H < \max^I > \max^J$
$\Delta T$	$\max^A < \max^B > \max^C > \max^D > \max^E$	$\max^F > \max^G > \max^H > \max^I \approx \max^J$
$TwrBsMyt$	$S_{eq}^A > S_{eq}^B < S_{eq}^C < S_{eq}^D < S_{eq}^E$	$S_{eq}^F > S_{eq}^G > S_{eq}^H > S_{eq}^I > S_{eq}^J$
$TwrBsMxt$	$S_{eq}^A > S_{eq}^B < S_{eq}^C < S_{eq}^D < S_{eq}^E$	$S_{eq}^F < S_{eq}^G > S_{eq}^H > S_{eq}^I > S_{eq}^J$
$\Delta T$	$S_{eq}^A > S_{eq}^B \approx S_{eq}^C > S_{eq}^D > S_{eq}^E$	$S_{eq}^F > S_{eq}^G > S_{eq}^H > S_{eq}^I > S_{eq}^J$
$RootMyb1$	$S_{eq}^A > S_{eq}^B < S_{eq}^C < S_{eq}^D > S_{eq}^E$	$S_{eq}^F > S_{eq}^G > S_{eq}^H > S_{eq}^I > S_{eq}^J$
$RootMxb1$	$S_{eq}^A < S_{eq}^B = S_{eq}^C = S_{eq}^D = S_{eq}^E$	$S_{eq}^F \approx S_{eq}^G \approx S_{eq}^H < S_{eq}^I < S_{eq}^J$

**TABLE A10 Analysis of the ultimate loads  $\max^w$  and fatigue loads  $S_{eq}^w$  resulting from five different wind speed observers regarding the steady increase or decrease of the loads (comparing both Lyapunov approaches with each other with  $w \in [A, E]$  for the global wind speed observers and with  $w \in [F, J]$  for the local wind speed observers; based on the loads depicted in Figure 8).**

Loads	A $\leftrightarrow$ F	B $\leftrightarrow$ G	C $\leftrightarrow$ H	D $\leftrightarrow$ I	E $\leftrightarrow$ J
$TwrBsMyt$	$\max^A > \max^F$	$\max^B < \max^G$	$\max^C < \max^H$	$\max^D > \max^I$	$\max^E > \max^J$
$TwrBsMxt$	$\max^A > \max^F$	$\max^B < \max^G$	$\max^C < \max^H$	$\max^D > \max^I$	$\max^E > \max^J$
$RootMyb1$	$\max^A < \max^F$	$\max^B > \max^G$	$\max^C > \max^H$	$\max^D > \max^I$	$\max^E > \max^J$
$RootMxb1$	$\max^A > \max^F$	$\max^B < \max^G$	$\max^C < \max^H$	$\max^D > \max^I$	$\max^E > \max^J$
$\Delta T$	$\max^A < \max^F$	$\max^B > \max^G$	$\max^C > \max^H$	$\max^D > \max^I$	$\max^E < \max^J$
$TwrBsMyt$	$S_{eq}^A > S_{eq}^F$	$S_{eq}^B < S_{eq}^G$	$S_{eq}^C < S_{eq}^H$	$S_{eq}^D > S_{eq}^I$	$S_{eq}^E > S_{eq}^J$
$TwrBsMxt$	$S_{eq}^A > S_{eq}^F$	$S_{eq}^B < S_{eq}^G$	$S_{eq}^C < S_{eq}^H$	$S_{eq}^D > S_{eq}^I$	$S_{eq}^E > S_{eq}^J$
$RootMyb1$	$S_{eq}^A < S_{eq}^F$	$S_{eq}^B < S_{eq}^G$	$S_{eq}^C > S_{eq}^H$	$S_{eq}^D > S_{eq}^I$	$S_{eq}^E > S_{eq}^J$
$RootMxb1$	$S_{eq}^A > S_{eq}^F$	$S_{eq}^B > S_{eq}^G$	$S_{eq}^C > S_{eq}^H$	$S_{eq}^D < S_{eq}^I$	$S_{eq}^E < S_{eq}^J$
$\Delta T$	$S_{eq}^A > S_{eq}^F$	$S_{eq}^B < S_{eq}^G$	$S_{eq}^C > S_{eq}^H$	$S_{eq}^D > S_{eq}^I$	$S_{eq}^E > S_{eq}^J$