



Corrigendum: Analysis of Failure Models and Deformation Evolution Process of Geological Hazards in Ganzhou City, China

Qinghua Zhan^{1,2}, Shimei Wang^{1,2}, Li Wang^{1,2*}, Fei Guo^{1,2}, Daipeng Zhao³ and Jinzhou Yan^{1,2}

¹Key Laboratory of Geological Hazards on the Three Gorges Reservoir Area, Ministry of Education, China Three Gorges University, Yichang, China, ²National Field Observation and Landslides Research Station in the Three Gorges Reservoir Area, China Three Gorges University, Yichang, China, ³China Yangtze Ecology and Environment Co. Ltd., Wuhan, China

Keywords: geohazards, landslides, landslide-prone rocks, slope failure mode, *in-situ* model test, numerical simulation

OPEN ACCESS

Edited and reviewed by:

Faming Huang,
Nanchang University, China

*Correspondence:

Li Wang
wangli_ctgu@126.com

Specialty section:

This article was submitted to
Geohazards and Georisks,
a section of the journal
Frontiers in Earth Science

Received: 27 August 2021

Accepted: 17 September 2021

Published: 01 October 2021

Citation:

Zhan Q, Wang S, Wang L, Guo F,
Zhao D and Yan J (2021) Corrigendum:
Analysis of Failure Models and
Deformation Evolution Process of
Geological Hazards in Ganzhou
City, China.
Front. Earth Sci. 9:765392.
doi: 10.3389/feart.2021.765392

A Corrigendum on

Analysis of Failure Models and Deformation Evolution Process of Geological Hazards in Ganzhou City, China

by Zhan, Q., Wang, S., Wang, L., Guo, F., Zhao, D., and Yan, J. (2021). *Front. Earth Sci.* 9:731447. doi: 10.3389/feart.2021.731447

In the original article, there was a mistake in **Table 3** “Rock and soil-mechanical parameters of discrete elements in each slope” as published.

The authors pasted duplicate data in **Table 3**, which caused the data in **Table 3** and **Table 2** to be duplicated. The corrected **Table 3** Rock and soil-mechanical parameters of discrete elements in each slope appears below.

The authors apologize for this error and state that this does not change the scientific conclusions of the article in any way. The original article has been updated.

Publisher’s Note: All claims expressed in this article are solely those of the authors and do not necessarily represent those of their affiliated organizations, or those of the publisher, the editors and the reviewers. Any product that may be evaluated in this article, or claim that may be made by its manufacturer, is not guaranteed or endorsed by the publisher.

Copyright © 2021 Zhan, Wang, Wang, Guo, Zhao and Yan. This is an open-access article distributed under the terms of the Creative Commons Attribution License (CC BY). The use, distribution or reproduction in other forums is permitted, provided the original author(s) and the copyright owner(s) are credited and that the original publication in this journal is cited, in accordance with accepted academic practice. No use, distribution or reproduction is permitted which does not comply with these terms.

TABLE 3 | Rock and soil-mechanical parameters of discrete elements in each slope.

Geographical location	Lithology	Rock properties	Normal stiffness K_n ($N \cdot m^{-1}$)	Tangential stiffness K_s ($N \cdot m^{-1}$)	Fracture displacement X_b (m)	Shear resistance F_{s0} (N)	Coefficient of friction μ_b
Shuitou Village, Ganzhou City	Triassic porphyritic granite	Strongly weathered soil	3.25E+06	5.84E+06	2.10E-05	3.54E+04	0.13
		Bedrock	2.52E+07	2.69E+07	5.88E-04	1.98E+06	0.75
Xinwuxia Village, Ganzhou City	Interbedded limestone and phyllite, Upper Sinian Laohutang Formation	Broken rock	8.12E+06	4.35E+06	7.81E-05	2.35E+05	0.28
		Bedrock	1.48E+07	1.43E+07	3.96E-04	8.96E+05	0.61
Kongmu Village, Ganzhou City	Interbedded limestone and phyllite, Upper Sinian Laohutang Formation	Broken rock	8.12E+06	4.35E+06	7.81E-05	2.35E+05	0.28
		Bedrock	1.48E+06	1.43E+07	3.96E-04	8.96E+05	0.61