



OPEN ACCESS

EDITED BY

Jinlong Liu,
Zhejiang University, China

REVIEWED BY

Xiaochen Wang,
Chang'an University, China
Nan Zhang,
Saint-Gobain Research North America,
United States

*CORRESPONDENCE

M. Masoudi,
✉ mansour.masoudi@emissol.com

RECEIVED 31 May 2024

ACCEPTED 14 June 2024

PUBLISHED 02 July 2024

CITATION

Meruva P, Matheaus A, Sharp CA, McCarthy JE Jr, Masoudi M, Poliakov N and Noorfeshan S (2024), Corrigendum: Meeting future NO_x emission regulations by adding an electrically heated mixer. *Front. Mech. Eng* 10:1441864. doi: 10.3389/fmech.2024.1441864

COPYRIGHT

© 2024 Meruva, Matheaus, Sharp, McCarthy, Masoudi, Poliakov and Noorfeshan. This is an open-access article distributed under the terms of the [Creative Commons Attribution License \(CC BY\)](https://creativecommons.org/licenses/by/4.0/). The use, distribution or reproduction in other forums is permitted, provided the original author(s) and the copyright owner(s) are credited and that the original publication in this journal is cited, in accordance with accepted academic practice. No use, distribution or reproduction is permitted which does not comply with these terms.

Corrigendum: Meeting future NO_x emission regulations by adding an electrically heated mixer

P. Meruva¹, A. Matheaus¹, C. A. Sharp¹, J. E. McCarthy Jr², M. Masoudi^{3*}, N. Poliakov³ and S. Noorfeshan³

¹Southwest Research Institute (SwRI), San Antonio, TX, United States, ²Eaton, Galesburg, MI, United States, ³Emissol LLC, Mill Creek, WA, United States

KEYWORDS

heated mixer, advanced aftertreatment, reduced NO_x emissions, electric heater, increase exhaust temperature, 130°C DEF injection

A Corrigendum on Meeting future NO_x emission regulations by adding an electrically heated mixer

by Meruva P, Matheaus A, Sharp CA, McCarthy JE Jr, Masoudi M, Poliakov N and Noorfeshan S (2022). *Front. Mech. Eng.* 8:991579. doi: 10.3389/fmech.2022.991579

In the published article, there was an error in [Tables 10, 11](#) as published. The units for BSNO_x and CO₂ were mislabeled as g/hp-hr instead of g/kW-hr. The corrected tables and their captions appear below.

The authors apologize for this error and state that this does not change the scientific conclusions of the article in any way. The original article has been updated.

Publisher's note

All claims expressed in this article are solely those of the authors and do not necessarily represent those of their affiliated organizations, or those of the publisher, the editors and the reviewers. Any product that may be evaluated in this article, or claim that may be made by its manufacturer, is not guaranteed or endorsed by the publisher.

TABLE 10 Cold WHTC test results.

Config	BSNO _x (g/kW-hr)			CO ₂ (g/kW-hr)	EHM system energy (kW-hr)
	EO	LO-SCR out	TP		
Baseline AT	3.98	1.53	0.245	678.8	—
AT + EHM system	4.28	0.56	0.091	686.5	0.80

TABLE 11 Hot WHTC test results.

Config	BSNO _x (g/kW-hr)			CO ₂ (g/kW-hr)	EHM system energy (kW-hr)
	EO	LO-SCR out	TP		
Baseline AT	5.00	2.08	0.125	659.2	—
AT + EHM system	5.43	0.69	0.001	662.7	0.57