



OPEN ACCESS

EDITED BY

Yong Jiang,
Fujian Agriculture and Forestry University,
China

REVIEWED BY

Panpan Liu,
Zhengzhou University,
China
Xiang Qi,
Tsinghua University,
China

*CORRESPONDENCE

Jinxing Ma
jinxing.ma@gdut.edu.cn

SPECIALTY SECTION

This article was submitted to
Microbiotechnology,
a section of the journal
Frontiers in Microbiology

RECEIVED 12 October 2022

ACCEPTED 01 November 2022

PUBLISHED 18 November 2022

CITATION

Tao Y, Liu Z, Zheng J, Zhou J, He D and
Ma J (2022) Microalgae production in
human urine: Fundamentals, opportunities,
and perspectives.
Front. Microbiol. 13:1067782.
doi: 10.3389/fmicb.2022.1067782

COPYRIGHT

© 2022 Tao, Liu, Zheng, Zhou, He and Ma.
This is an open-access article distributed
under the terms of the [Creative Commons
Attribution License \(CC BY\)](https://creativecommons.org/licenses/by/4.0/). The use,
distribution or reproduction in other
forums is permitted, provided the original
author(s) and the copyright owner(s) are
credited and that the original publication in
this journal is cited, in accordance with
accepted academic practice. No use,
distribution or reproduction is permitted
which does not comply with these terms.

Microalgae production in human urine: Fundamentals, opportunities, and perspectives

Yewen Tao¹, Zhipeng Liu², Junjian Zheng³, Jieqin Zhou¹, Di He¹ and Jinxing Ma^{1*}

¹Key Laboratory for City Cluster Environmental Safety and Green Development of the Ministry of Education, School of Ecology, Environment and Resources, Guangdong University of Technology, Guangzhou, China, ²School of Environmental Science and Engineering, Guangdong University of Technology, Guangzhou, China, ³College of Life and Environmental Sciences, Guilin University of Electronic Technology, Guilin, China

The biological treatment of source-separated human urine to produce biofuel, nutraceutical, and high-value chemicals is getting increasing attention. Especially, photoautotrophic microalgae can use human urine as media to achieve environmentally and economically viable large-scale cultivation. This review presents a comprehensive overview of the up-to-date advancements in microalgae cultivation employing urine in photobioreactors (PBRs). The standard matrices describing algal growth and nutrient removal/recovery have been summarized to provide a platform for fair comparison among different studies. Specific consideration has been given to the critical operating factors to understand how the PBRs should be maintained to achieve high efficiencies. Finally, we discuss the perspectives that emphasize the impacts of co-existing bacteria, contamination by human metabolites, and genetic engineering on the practical microalgal biomass production in urine.

KEYWORDS

microalgae, urine, photobioreactor, biomass, ammonia, resource recovery

Introduction

Urine contains a large amount of nitrogen, phosphorus, potassium and other nutrients. While contributing to only 1% of the total volume of sewage, human urine accounts for 80% and 40%–50% of the total nitrogen and phosphate loads, respectively (Wilsenach et al., 2007). Conventional management of urine in wastewater treatment is not only energy-intensive (e.g., at an energy cost of 45 MJ kg-N⁻¹ and 49 MJ kg-P⁻¹) but also leads to the loss of nitrogen and phosphorus resources through waste discharge (Maurer et al., 2003; Liu Z. et al., 2008). As a result, a separate collection of urine has presented an exciting alternative to sewage management (Nazari et al., 2020). For example, no-mix technology can produce source-separated urine that only contains water, urea and inorganic salts (e.g., Ca²⁺ and Mg²⁺; Wilsenach and van Loosdrecht, 2006), which has been considered a promising but unexploited stock for N and P fertilizers for agriculture (Larsen et al., 2021). Therefore, we envision that source separation and utilization of urine can not only improve the

sustainability of sewage management but also add the potential to achieve the minimum environmental impacts over a fertilizer life cycle.

Conventional treatment processes, including stripping, physical adsorption, and chemical precipitation, have been deployed to manage urine and separate nutrients; however, they suffer from the process limitations such as high energy consumption, significant chemical dose, and ammonia loss (Zhang et al., 2018). Alternatively, the biological treatment of urine, mainly to produce biofuel, nutraceutical and high-value chemicals is getting increasing attention (Soares et al., 2013). Microalgae are photoautotrophic microorganisms that take up and accumulate nutrients using light as an energy source and carbon dioxide as an inorganic carbon source (Tuantet, 2015). The cultivation of microalgae requires nutrients, primarily N and P. In addition, the urine also comprises trace elements (e.g., B, Cu, Zn, Mo, Fe, Co and Mn) that are necessary for algal growth. Furthermore, human urine typically contains no hazardous chemical compounds or heavy metals (Rodushkin and Ödman, 2001; Gòdia et al., 2002). To this end, using source-separated urine as media has been a practice for environmentally and economically viable large-scale microalgae cultivation for biofuel production.

According to the literature available, Tuantet et al. (2013) pioneered the cultivation of microalgae in non-diluted human urine, in which fresh and synthetic urine was first demonstrated to support the rapid growth of *Chlorella sorokiniana*, highlighting the significance of economically large-scale microalgae production in human urine (Tuantet et al., 2013). Jaatinen et al. (2016) also successfully cultivated *Chlorella vulgaris* in 100-times diluted urine at the highest biomass density of 0.60 gL⁻¹. Following attempts have been carried out employing various species such as *Spirulina* and *Scenedesmus acuminatus*. Moreover, microalgae production in human urine also achieves the removal and recovery of nutrients (i.e., N and P). In the study by Chang et al. (2013), 97% of ammonium nitrogen, 96.5% of the total phosphorus (TP) and 85%–98% of urea in diluted urine could be removed by microalgae, the practice of which has closed the gap between waste management and sustainable resource exploitation (Behera et al., 2020). With regard to the challenges in biomass separation from the dilute media, a membrane photobioreactor (MPBR) has been proposed and deployed for the continuous cultivation of microalgae (Nguyen et al., 2021). An unofficial Scopus search of the literature on “(Micro)algae” and “Urine” was carried out for the timeline from 2000 to 2022 (Figure 1), with the results demonstrating a quick increase in the publication number in the past decade. While recent progress in microalgae breeding and reactor design has improved the economic and process efficiencies of biomass production on human urine (Yang et al., 2011; Chatterjee et al., 2019), there are still challenges in bringing this idea into fruition, including low-cost recovery of microalgae cells, high-efficient extraction of the biofuel, and scale-up of the photobioreactors.

To this end, a comprehensive understanding of the fundamentals, opportunities and perspectives of microalgae




FIGURE 1
Survey of the publications (Elsevier Scopus) in topics related to “(Micro)algae” and “Urine” from 2000 to 2022 (Accessed date: October 29, 2022). Line serves to guide the eye.

production in urine is of great significance. This Review sheds light on the advancements in microalgae cultivation on synthetic and human urine in photobioreactors. We systematically summarized the matrices that describe the algal growth and nutrient removal/recovery. Specific consideration has been given to the critical operating parameters influencing the process performance. Finally, we discuss the perspectives that emphasize the future research interest in the field.

Urine, microalgae and photobioreactors

Compositions of synthetic and natural urine

Human urine is composed of eight main ionic/non-ionic species (i.e., Na⁺, K⁺, Ca²⁺, Cl⁻, SO₄²⁻, H₂PO₄⁻/HPO₄²⁻, HCO₃⁻ and urea; Golder et al., 2007). Most nitrogen in fresh urine originates from urea, which can be hydrolyzed into free ammonia (NH₃), ammonium (NH₄⁺) and bicarbonate (HCO₃⁻) during storage. Both urea and ammonium are known to support the growth of microalgae (Tuantet, 2015). However, the free ammonia in urine can inhibit the growth of microalgae (Tuantet et al., 2013), and cell death may occur in the presence of high ammonia concentrations (Belkin and Boussiba, 1991). Piltz and Melkonian (2017) found satisfactory algal growth for all dilutions but not for undiluted urine. Thus, diluting synthetic or natural urine is essential to reduce ammonia's toxic effect (Azov and Goldman, 1982). Cultivating microalgae in urine has two scenarios. The first scenario is a continuous culture by adding fresh urine as a daily nutrient stock (Tuantet et al., 2013). A process parameter, dilution rate (D , h⁻¹), is introduced to express the relationship between the flow of the raw urine (q , L h⁻¹) and the volume of the bioreactor (V , L). The other is a batch cultivation by employing diluted urine

at a lower light intensity (Jaatinen et al., 2016), in which a parameter of dilution (or dilution ratio) is used (Tuantet et al., 2019).

Synthetic urine

Nitrogen sources in synthetic urine generally include ammonium, nitrate (hydrolysis) and urea. Hulatt et al. (2012) showed that the growth of *C. vulgaris* in a medium containing urea as the nitrogen source had a slightly higher maximum rate and yield than that with nitrate; however, no growth was observed with ammonium. The proposed explanation related to the ammonium utilization causing a significant decrease in the medium pH (e.g., from 6.8 to 4.0), thus resulting in the cessation of microalgae growth (Hulatt et al., 2012). In contrast, according to the earlier experimentation conducted by Schuler et al. (1953), *C. vulgaris* may prefer ammonium over nitrate as the nitrogen source. Trace elements added to synthetic urine include ethylene diamine tetraacetic acid (EDTA) ferric sodium salt, H_3BO_3 , Mn(II), Zn(II) and Cu(II) (Tuantet, 2015). Chang et al. (2013) indicated that both fresh and synthetic urine might sustain rapid algal growth if additional trace elements such as Cu, Fe, Mn and Zn were dosed. Examples of synthetic urine used in microalgae cultivation are summarized in Table 1. As shown, the synthetic urine is commonly diluted 10–20 times upon use in batch studies, reducing ammonium inhibition while providing sufficient nutrients for microalgae growth. In comparison, *C. sorokiniana* could grow on pure urea and the algae growth would not be inhibited by ammonium up to a concentration of 1,400 mg $NH_4^+-N L^{-1}$ at pH lower than 8.0 (Tuantet et al., 2013).

Human urine

At 20°C, hydrolysis of ~64% of the urea in fresh human urine to ammonia and carbon dioxide occurs within 4 days (Adamsson, 2000). When hydrolyzed urine instead of fresh urine is used for cultivation, additional elements (e.g., Mg) may be required. In most cases, when urine is hydrolyzed, the N/P ratio increases due to the precipitation of phosphate (Chang et al., 2013; Tuantet et al., 2013). The compositions of real human urine samples are presented in Table 1. Similar to the problem existing in synthetic urine, microalgae growth in real urine suffers from inhibition from salt and nitrogen compounds, especially when free ammonia concentration is above 140 mg L^{-1} and/or nitrate concentration above 1,000 mg L^{-1} (Larsen et al., 2021). In batch studies, the dilution of human urine for microalgae cultivation is 5–100. While the proportion of viable cells in the biomass produced from less diluted urine was allegedly higher due to the abundant nutrients (Jaatinen et al., 2016), the chemistry condition in concentrated urine would prompt the precipitation of some critical elements (e.g., Fe^{2+} , a component required for the synthesis of chlorophyll), thereby decreasing the overall microalgal growth and nutrient accumulation in the biomass (Tuantet et al., 2013). For example, in batch tests, *Scenedesmus* could grow at 10-time dilution (i.e., an initial NH_3-N concentration of ~200 mg L^{-1}) but not at lower dilutions, however, sustainable growth was only

observed at 20-time dilution (at ~100 mg $NH_3-N L^{-1}$; Chatterjee et al., 2019). Thus, applying an optimized pre-dilution to pure urine is crucial before microalgae cultivation in a photobioreactor (Tuantet et al., 2019). In continuous cultivation, in contrast to the optimum dilution rate for synthetic urine ranging between 0.10 and 0.15 h^{-1} , the algal growth in human urine demonstrates a higher efficiency at a dilution rate of 0.05 h^{-1} than at 0.10 h^{-1} (Tuantet, 2015). While biomass productivity could be higher at a dilution rate between 0.1 and 0.2 h^{-1} , the nitrogen removal efficiency is compromised (Tuantet et al., 2019). In addition, an investigation has been conducted to assess whether differences in gender-related components, e.g., sex hormones, can influence the microalgae growth (Tuantet, 2015). Results showed that the impact was insignificant. Contamination of human urine by bacteria and the unmetabolized drug is another challenge for microalgae cultivation. Various bacteria were detected in *C. vulgaris* cultures employing sterilized or non-sterilized media, indicating that bacteria may play an essential role in microalgae growth in urine (Lakaniemi et al., 2012). As for trace drugs, pretreatment of urine with activated carbon can eliminate the potentially harmful effects (Piltz and Melkonian, 2017).

Microalgae species

Via uptake and conversion of nutrients, microalgae enable urine purification and resource recovery in biofuels, biochemicals, and bio-fertilizer (Tuantet, 2015). As for biomass production, microalgae can grow autotrophically by utilizing organic/inorganic nitrogen and CO_2 /bicarbonate as carbon sources. Meanwhile, microalgae cells can directly use phosphate in urine under aerobic conditions and transform it into adenosine triphosphate (ATP) or other organic substances through assimilation and proliferation (Yang et al., 2008). Figure 2 presents the microalgae species successfully cultivated in synthetic and real human urine. Some typical species and their characteristics are summarized as follows:

Chlorella is a fast-growing microalgae species with reported maximum specific growth up to 0.25 h^{-1} under autotrophic and light saturating conditions (Cuaresma et al., 2009), the dry weight of which is contributed by 6%–8% nitrogen and 1%–2% phosphorus. Microalgae biomass of *Chlorella* can be directly used as a fertilizer and/or a potential source for chemicals and biofuels (Tuantet et al., 2013). Because *Chlorella* is rich in protein (Adamsson, 2000), the cultivated biomass from urine can be directly fed to zooplankton and the latter can be provided to fish in the constructed food chain (Adamsson, 2000). The widely investigated *Chlorella* in urine media includes *C. sorokiniana* and *C. vulgaris* (Figures 2A,B). *C. vulgaris* has higher Omega-3 fatty acids content. These fatty acids are commonly found in green leafy vegetables and oily fish such as herring, sardines, and tuna (Revellame et al., 2021). *C. vulgaris* prefers ammonium to nitrate as a source of nitrogen, which benefits the growth in urine (Schuler et al., 1953). Another species of *Chlorella*, *C. sorokiniana*


TABLE 1 Compositions of cultivation media used for microalgae.

Cultivation devices	Cultivation media	N source ¹ or hydrolyzed state ^{2,a}	TN or NH ₄ ⁺ -N, ^b mgL ⁻¹	TP or PO ₄ ³⁻ -P, mgL ⁻¹	COD, mgL ⁻¹	Dilution	Refs.	
Algal tanks	RHU	Unhydrolyzed ²	11,450/500	850/n.a.	n.a.	50	Adamsson (2000)	
24-well microtiter plates	SHU	Urea ¹	5,370/n.a.	n.a./733	1,428	5, 10	Tuantet et al. (2013)	
	RHU	Unhydrolyzed ²	6,340/442	401/n.a.	7,480	5, 10		
Blue cap bottle	RHU	Unhydrolyzed ²	6,500/361	510/n.a.	6,305	5, 10		
	RHU	n.a.	4,850 ± 1,730/n.a.	155 ± 65/n.a.	n.a.	3/4, n.d., 2, 4	Zhang et al. (2014)	
Erlenmeyer flasks	SHU	Urea ¹	305/n.a.	21.2/n.a.	n.a.	n.d.	de Wilt et al. (2016)	
	RHU	Hydrolyzed ²	5,124/3,240	151.2/n.a.	n.a.	6		
	SHU	Urea ¹	109.8/n.a.	13.0/n.a.	n.a.	n.d.	Yang et al. (2008)	
	RHU	Unhydrolyzed ²	4320/275	355/n.a.	n.a.	25, 75, 100, 150, 300	Jaatinen et al. (2016)	
	RHU	Unhydrolyzed ²	6,800/520	670/n.a.	n.a.	n.d.,100		
Transparent flasks	Livestock	Ammonium ¹	15.4 ± 0.3/13.4 ± 0.5	0.7 ± 0.0/n.a.	111.9 ± 16.7	n.d.	Kim and Kim (2017)	
Outdoor raceway	RHU	Hydrolyzed ²	3,480 ± 130/1,800 ± 750	190 ± 52/n.a.	5,500 ± 200	n.d., 2, 3, 4, 5, 10, 15, 20, 25	Chatterjee et al. (2019)	
Tubular/bubble column	Piggery	Ammonium ¹	162.0 ± 8.0/n.a.	209.0 ± 5.5/n.a.	3,700 ± 51	n.d.	Zhu et al. (2013)	
PBR ^c	Swine	Ammonium ¹	510 ± 10/460 ± 15	76.1 ± 5.0/36.7 ± 7.3	5,200 ± 900	2	Chen et al. (2020)	
	SHU	Ammonium ¹	n.a./6,000	600/n.a.	n.a.	120	Chang et al. (2013)	
Flat/Panel PBR	RHU	Hydrolyzed ²	8,000 – 10,000/2,500–8,100	700–2,000/n.a.	8,000–10,000	120		
	RHU	Hydrolyzed ²	8,880/6,000	792/n.a.	9,960	120		
	SHU	Urea ¹	109.8/n.a.	13.0/n.a.	n.a.	n.d.	Yang et al. (2008)	
	Swine	Ammonium ¹	501.27	39.12	321.4	2	Cheng et al. (2020)	
	SHU	Ammonium ¹	4,326/4,005	n.a./255	n.a.	2–50	Tuantet et al. (2014)	
	RHU	Unhydrolyzed ²	7,167/844	466/n.a.	8,349	2, 3, 5, 10, 20, 50		
	RHU	Unhydrolyzed ²	4,358/393	200/n.a.	2,886			
	RHU	Hydrolyzed ²	5,310/4660	260/n.a.	5,160			
	SHU	Ammonium ¹	6,990/n.a.	n.a./620	n.a.	1.8–10	Tuantet (2015)	
	RHU	Unhydrolyzed ²	2,260/312	n.a./215	2,520	5, 10, 20		
MPBR	RHU	Hydrolyzed ²	3,550/733	n.a./387	4,885	5, 10, 20		
	RHU	Hydrolyzed ²	3,500/3,260	n.a./341	3,555	5, 10, 20		
	RHU	Hydrolyzed ²	2,220/2,150	n.a./295	2,795	5, 10, 20		
	RHU	n.a.	2,626/n.a.	146/n.a.	3,270	1.8–8.5	Tuantet et al. (2019)	
	RHU	Hydrolyzed ²	5,015 ± 209/2258 ± 43	345 ± 2/n.a.	n.a.	30	Nguyen et al. (2021)	
	Twin-layer PBR	RHU	n.a.	5,760/n.a.	290/n.a.	n.a.	n.d., 5, 10	Piltz and Melkonian (2017)
		RHU	n.a.	3,700/n.a.	210/n.a.	n.a.		
		RHU	n.a.	2,500/n.a.	170/n.a.	n.a.		

^aWithout specification, ammonia/ammonium insignificantly (~10%) contributes to the total nitrogen in unhydrolyzed human urine; SHU, syntenic human urine; RHU, real human urine; ammonium indicates that ammonium was used as N source, and urea indicates that urea was used as N source. n.a. represents “not available”. Superscript numbers, 1: N source in synthetic urine including urea and ammonium. 2: Whether the human urine was hydrolyzed before the tests.

^bConcentrations shown in the table were the values before dilution; n.d., no dilution; TN, total nitrogen; TP, total phosphorus; COD, chemical oxygen demand.

^cPBR, photobioreactor; MPBR, membrane photobioreactor.



shows great potential for commercial production as a nutrient substitute for humans and animals (Morais Junior et al., 2020). *C. sorokiniana* is mesophilic, the growth of which is characterized by a relatively high optimal temperature (30°C–40°C) and a maximum specific growth rate of $\sim 0.27 \text{ h}^{-1}$ (Cuaresma et al., 2009). Furthermore, *C. sorokiniana* can synthesize neutral oil as triacylglycerol under stress conditions (e.g., under high light intensity or nutrient deficiency). The study by Tuantet et al. (2014) demonstrated that dilution of urine by two times could achieve adequate incubation of *C. sorokiniana* CCAP211/8K, which contributed to >90% of total nitrogen and phosphorus removal. Of all the commercial microalgae, while *Chlorella* has the second largest annual production inferior to *Spirulina*, the price of *Chlorella* is significantly higher on the market (Yuan et al., 2022).

Spirulina is the benchmark of microalgal biotechnology and is currently the most (3,000 dry tons annually) commercially produced microalgae (Detrell et al., 2020). *Spirulina* (*Arthrospira platensis*; Figures 2C,D), one of the essential cyanobacteria, produces high concentrations of pigments (chlorophyll a and phycocyanin), fatty acids (i.e., γ -linolenic acid) and proteins (Gutierrez-Salmeán et al., 2015). *A. platensis* contains a more balanced ratio of saturated to unsaturated fatty acids including Omega-3 and Omega-6 (Revellame et al., 2021). Moreover, *S. platensis* has a relatively high cell growth rate and requires an easy process for biomass recovery as a result of the filamentous cell

structure. Studies have demonstrated that the cultivation of *S. platensis* is viable for waste purification or aquatic food production (Chang et al., 2013). For example, *S. platensis* was harvested after 7 days of incubation and percentage removal of 97.0% and 96.5% was, respectively, achieved for NH_4^+ -N and total phosphorus in the urine at a 120-dilution (Chang et al., 2013).

Scenedesmus acuminatus is also widely used in the treatment of anaerobic digestion effluents and secondary domestic wastewater (Figures 2E,F), because of its capacity to grow at a high biomass concentration of 8–11 g L^{-1} (Posadas et al., 2015; Tao et al., 2017b). *Scenedesmus* is one of the high protein content species, which contains 50%–56% protein, 10%–17% carbohydrate and 12%–14% lipid (Raeisossadati et al., 2020). For example, a strain of *Desmodesmus* sp. QL96 isolated from Tibet, China contains 17 amino acids (including 7 essential ones; Cheng et al., 2021). The properties of *Desmodesmus* highlight its commercial merits in biomass cultivation from urine. *Scenedesmus* species have been reported to take up high concentrations of nitrogen (273 mg L^{-1}) and phosphorus (58.8 mg L^{-1} ; Kim et al., 2015). *Scenedesmus* was grown in 0.5% diluted urine supplemented with EDTA and iron, and its maximum biomass density was about 133 $\text{mg-dry weight L}^{-1}$.

Architecture of photobioreactors

Microalgae are generally cultivated in open or closed systems (Song et al., 2018). Raceway ponds are traditional open systems to cultivate microalgae (Table 1). While these configurations have merits including low cost and simple operation, microalgal productivity in open systems is highly susceptible to environmental conditions. In comparison, closed systems including tubular, flat panel and bubble column photobioreactors (PBRs) are relatively costly and currently limited to small-scale microalgae cultures that generate high-value products including poly-unsaturated fatty acids, carotenoids and other chemicals for pharmaceutical and cosmetics industries (Rezvani et al., 2022). The operating cost for closed reactors relates to collecting culture fluid and microalgae cells. Recent advancements in reactor design have paved the way for more efficient enrichment and collection of microalgae (Zittelli et al., 2013; Tuantet, 2015). The architectures of PBRs for microalgae cultivation in urine are summarized in Figure 3 and Table 2.

PBRs constructed for microalgae cultivation should sustain fast reaction rates, stable operation performance and a high capacity to recover nutrients via microalgae harvesting (Yang et al., 2008). In earlier experiments, Tuantet et al. (2013) cultured *Chlorella* on human and artificial urine microtiter plates. Column PBRs have simple configurations and better flow conditions (Figure 3A and Table 2). However, some practical problems exist when urine is used as feed. In addition to the nutrient levels of raw urine being unsuitable for algal growth, the dark color of urine and the low light penetration would challenge the PBR setup. To overcome the limitations, on the one hand, the bioreactors are




TABLE 2 Summary of photobioreactors (PBR) and operating parameters for biomass culture in urine.

PBR types	Parameters of PBR	Illumination		Aeration	Light intensity	T (°C)	Refs
		Source	Switch				
Column PBR	n.a. ^b	Red (620 nm) LED	n.a.	1% CO ₂	300 μmol m ⁻² s ⁻¹	30	Yang et al. (2008)
	1.2 L (60 cm height, 7.2 cm diameter)	Concentric fluorescent lamp	14 h:10 h	CO ₂ : 3 L min ⁻¹	444.4 W m ^{-2a}	30	Chang et al. (2013)
Flat/panel PBR	Flat panel with a vertical baffle (as shown by the right reactor): 0.925 L, 420 × 225 (mm)	High-pressure sodium lamps	n.a.	CO ₂ : 5% v/v, 1, 0.76, 0.67 LL ⁻¹ min ⁻¹	490– 1,550 × 2 μmol m ⁻² s ⁻¹	35/38	Tuantet et al. (2014)
	0.92 ± 0.12 L	High-pressure sodium lamps	n.a.	CO ₂ : 8%–20%	n.a.	38	Tuantet (2015)
	0.90 L	High-pressure sodium lamps	12 h:12 h	CO ₂ : 8%–20% v/v	1,530 μmol m ⁻² s ⁻¹	38	Tuantet et al. (2019)
Membrane PBR	Two PBRs with a diameter of 100 mm and a height of 600 mm, 4 L each. A hollow fiber membrane (MF) module (width × height = 95 mm × 320 mm, working surface area of 0.05 m ²).	n.a.	24 h: 24 h	CO ₂ gas/air mixture at 2 L min ⁻¹ with 2.5% (v/v) of CO ₂ .	3,000 lux	n.a.	Nguyen et al. (2021)

^a1 W m⁻² = 4.5 μmol m⁻² s⁻¹.

^bn.a. represents “not available.”

typically fed with diluted urine. Conversely, an optimized system requires shorter light paths for microalgae growth. In the study by Chatterjee et al. (2019), extremely high dilution would be necessary even for only 50% nitrogen recovery in a 0.5 m deep raceway pond. To this end, a short light-path PBR (typically in the flat-panel configuration, Figure 3B) has been developed to supply light to all cells encapsulated inside the microalgal culture and thus support dense cultivation. Continuous microalgae cultivation has been carried out in a PBR with a narrow light path (i.e., 5 mm). However, an inherent conflict remained between the nitrogen removal and photosynthetic efficiency when the PBR was used to treat urine containing 0.77–2.6 g-N·L⁻¹. Because an increase in the biomass

concentration/density would shield the illumination and create a “dark zone” for a considerable part of the culture, advancements to minimize the “dark zone” in order to enhance biomass productivity are of significance in a short light-path PBR (Tuantet, 2015).

From a theoretical perspective, cultivation at a high cell density is essential to sustain high nutrient removal efficiencies in urine treatment (Tuantet et al., 2014). A PBR employing a higher hydraulic retention time (HRT) can prompt biomass growth and nutrient removal, but this may require a larger volume/footprint for reactor deployment. To address this issue, the membrane separation process has been integrated with PBR to increase the capacity and improve biomass recovery efficiency (Ma et al., 2017; Nguyen et al.,

2021; i.e., membrane PBR in Figure 3C and Table 2). While membrane modules used in PBRs could be similar to those in conventional membrane bioreactors, the operating protocols may differ due to the characteristics of microalgae. For instance, the formation of a cake layer on the membrane surface in PBRs could be deemed as a means to recover the suspended cells from the dilute culture, which may pave the way for the application of dynamic membrane processes in membrane PBRs for more-efficient biomass harvesting (Ma et al., 2013b). Developing a realistic PBR with a compact structure is therefore one of the most critical interests in microalgae production in human urine (Larsen et al., 2021).

Standard matrices to evaluate microalgae growth and nutrient removal/recovery

Cell growth and biomass production

Specific growth rate

The specific growth rate (μ , h^{-1}) of microalgae production in urine can be calculated by linear regression of the natural logarithm of optical density (OD) as a function of culturing time according to the following equation (Equation 1; Chang et al., 2013):

$$\mu = \frac{\ln\left(\frac{N_2}{N_1}\right)}{t_2 - t_1} \quad (1)$$

where N_1 and N_2 represent the OD of a predetermined wavelength [e.g., 750 nm (Tuantet et al., 2013)] at t_1 and t_2 respectively. For instance, the growth rates (0.20–0.38 day^{-1}) of *C. vulgaris* cultured in urine at different dilutions (i.e., 1:25–1:300) of urine were determined using Equation 1, which were compared to that obtained in Chu-10 medium (0.37 day^{-1} ; Jaatinen et al., 2016). Note that either biomass (X , g L^{-1}) or Chlorophyll *a* (Chl *a*) concentration (C_{chl} , mg L^{-1}) can be alternatively introduced into Equation 1 to estimate the specific growth rate (Porra et al., 1989).

Biomass productivity

The successful implementation of microalgae as a potential bio-energy feedstock depends on the biomass yield. For example, Yang et al. (2008) found that, in the batch culture of *Spirulina*, 1.05 g biomass could be obtained by treating 12.5 ml synthetic human urine. The standard parameter describing biomass productivity (β , $\text{g L}^{-1} \text{ day}^{-1}$) in batch reactors is given in Equation 2 (Gao et al., 2018; Nguyen et al., 2020a,b):

$$\beta = \frac{X_t}{\text{BRT}} \quad (2)$$

where X_t is the biomass concentration in a photobioreactor, and BRT is the biomass retention time (day; Chatterjee et al.,

2019; Tuantet et al., 2019). X_t can be determined by employing the standard plate count method (counts ml^{-1}), flow cytometry (counts ml^{-1}), weighing of the volatile suspended solids (g L^{-1} ; Jaatinen et al., 2016) or calibration conversion of the OD values [i.e., $X_t = 0.3421 \times \text{OD}_{750}$ for *C. sorokiniana* (Zittelli et al., 2013; Tuantet, 2015)]. We summarized the X_t and β values describing algal production in different literature in Table 3, and the results indicated that a higher β (9.3–14.8 $\text{g L}^{-1} \text{ day}^{-1}$) was observed at low dilution (i.e., no dilution or dilution ratio = 2). Moreover, when a PBR is operated in continuous mode and at a steady state (i.e., when there is no accumulation of biomass in the reactor), the volumetric biomass productivity (β_{vol}) is determined based on the biomass dry weight concentration (X_v , g L^{-1}) and the reactor dilution rate (D , h^{-1} ; Tuantet et al., 2019; Equation 3), which can be converted to the area productivity (P_{area}) by integrating the reactor dimensions (Equation 4):

$$\beta_{\text{vol}} = X_t D \quad (3)$$

$$P_{\text{area}} = \frac{1000 \beta_{\text{vol}}}{\text{SVR}} \quad (4)$$

where SVR is the surface area to volume ratio (m^{-1}). When the microalgae community in urine is at the logarithmic phase, the net specific microalgae growth rate, dX/dt , is given in Equation 5:

$$\frac{dX}{dt} = (\mu - D) X_t \quad (5)$$

Photosynthetic and harvesting efficiencies

Since the additional light source is widely implemented for microalgae production in urine, the observed biomass yield can be normalized to the lighting energy to assess the photosynthetic efficiency (Y_{ph} , $\text{g mol}_{\text{ph}}^{-1}$; Equation 6):

$$Y_{\text{ph}} = \frac{X_t q}{I_{\text{phin}} 24 A_r} = \frac{X_t q}{I_{\text{phin}} \times 10^{-6} \times 24 \times 3600 \times A_r} \quad (6)$$

where q is the liquid flow (L day^{-1}), $I_{\text{phin}24}$ is the daily integral light intensity ($\text{mol}_{\text{ph}} \text{m}^{-2} \text{ day}^{-1}$), A_r is the reactor surface area (m^2) and I_{phin} is the average light intensity ($\mu\text{mol}_{\text{ph}} \text{m}^{-2} \text{ s}^{-1}$). In the study by Tuantet et al. (2019), the maximum Y_{ph} of *C. sorokiniana* CCAP211/8 K reached 0.97 $\text{g mol}_{\text{ph}}^{-1}$ at a dilution rate of synthetic urine between 0.10 and 0.15 h^{-1} , which is comparable to other studies using *C. sorokiniana* (Cuaresma et al., 2009; Holdmann et al., 2018). Following cultivation, settlement or separation processes (Tuantet et al., 2014) are applied to separate or recover microalgae cells from the dilute medium. The harvesting efficiency (η , %) is calculated by using Equation 7:

$$\eta = \frac{X_R V_R}{X_t V} \times 100 \quad (7)$$

where X_R is the biomass concentration in the recovered volume (V_R). V is the liquid volume of the photobioreactor.

Nutrients removal and recovery

Nutrient removal

Microalgae can absorb N and P nutrients into their cells at concentrations as low as 2.2 and 0.15 mg L⁻¹, respectively (Boelee et al., 2011). When urine is used as a nutrient medium to cultivate microalgae, three routines of assimilation, ammonia volatilization, and denitrification, contribute to nitrogen removal (Gao et al., 2016). The percentage removal (p_N , %) and removal rate (r_N , mg L⁻¹ day⁻¹) of nitrogen are, respectively, determined by Equations 8, 9:

$$p_N = \frac{C_{N,0} - C_{N,t}}{C_{N,0}} \times 100 \quad (8)$$

$$r_N = \frac{C_{N,0} - C_{N,t}}{t} \times 100 \quad (9)$$

where $C_{N,0}$ and $C_{N,t}$ are the nitrogen concentrations (mg L⁻¹) at $t=0$ and time t (day). In comparison, phosphorus removal/recovery during microalgae cultivation on urine relates to both assimilation by microalgal cells and precipitation induced by pH changes (Singh et al., 2015; Wang et al., 2017). The calculations of percentage removal and removal rate of phosphorus also refer to Equations 8, 9.

In a semi-continuous culture of *C. sorokiniana*, 84% removal of total nitrogen and nearly 100% removal of total phosphorus can be achieved via microalgae growth in fresh human urine (Zhang et al., 2014). Tuantet et al. (2014) demonstrated that the removal of nitrogen by microalgae cultivation (75%–85% or 1,000–1,300 mg L⁻¹) was comparable with conventional treatment technologies including nitrification and anaerobic ammonia oxidation (Udert et al., 2003). Likewise, when *S. platensis* was applied to swine wastewater, it was reported that ammonia removal ranged from 84% to 96% (Chang et al., 2013). Figure 4 summarizes the nitrogen and phosphorus removal by microalgae cultivation from urine in different literature (Adamsson, 2000; Yang et al., 2008; Chang et al., 2013; Tuantet et al., 2013, 2014, 2019; Zhu et al., 2013; Zhang et al., 2014; de Wilt et al., 2016; Jaatinen et al., 2016; Piltz and Melkonian, 2017; Chatterjee et al., 2019; Chen et al., 2020; Nguyen et al., 2021). Generally, a higher illumination/light intensity and a longer cultivation time (or BRT) would result in higher N and P removal. In comparison, the impacts of dilution (red circles: dilution >20, blue circles: dilution <10) and photobioreactor configurations were less significant.

Nutrient recovery

Microalgae can use nitrate and nitrite to synthesize amino acids, proteins and other substances (Vilchez and Vega, 1995).

Tuantet et al. (2014) showed that 85% of phosphorus and 90% of nitrogen could be recovered from urine by incorporation into biomass. Typically, the protein and lipid contents can be measured according to standard methods (Bahcegul et al., 2011; Chang et al., 2013) to estimate the conversion of nutrients in urine to biomass. For example, following cultivation in synthetic urine, the protein and lipid contents (% dry weight) obtained from *S. platensis* were 36.2% and 17.2%, respectively, (Chang et al., 2013), which were comparable with those (35.4% and 19.8%) obtained in real human urine. This was consistent with the conclusion drawn by Danesi et al. that the lipid content of *Spirulina* was not affected by the nitrogen source (Danesi et al., 2002). Data in Table 3 shows that the protein content (%) of the microalgae cultivated in urine generally ranges from ~35% to ~60% of the biomass with the lipid content varying in response to the medium composition and dilution.

Critical operating factors that influence the cultivation efficiency

According to the literature review, operating parameters including the light intensity, temperature, retention time, dose of trace elements and carbon source, and solution pH significantly impact the microalgae growth and conversion of nutrients to biomass. It is vital to investigate and determine the optimal operating conditions to prompt microalgae growth and resource recovery (Kinnunen and Rintala, 2016).

Light intensity and temperature

Light intensities and switch modes used for microalgae production in urine are summarized in Table 2. Essentially, light intensity influences the microalgae photosynthesis and consequently their growth rate via modulation of ATP and NADPH production and essential molecules synthesis. The study by Tuantet et al. (2013) indicated that illumination was one of the most important factors influencing algal growth and nutrients removal, which is also confirmed by the analysis in Figure 4. A biomass density of 6.6 g L⁻¹ was obtained in 2-times diluted urine at a light intensity of 1,540 μmol m⁻² s⁻¹ compared to that of 3.8 g L⁻¹ in 10-times diluted urine at 1050 μmol m⁻² s⁻¹ (Tuantet et al., 2014). Note that different illumination units (e.g., μmol m⁻² s⁻¹, W m⁻² and lux) have been used in the literature (Yang et al., 2008; Chang et al., 2013; Tuantet et al., 2014, 2019; Tuantet, 2015), and the photosynthetic photon flux density (μmol m⁻² s⁻¹) could be converted to lux by multiplying a factor of 54–82 (for sunlight and high-pressure sodium lamps) according to the manufacturer (for example, Apogee Instruments, Inc., UT, United States). Overall, it was suggested that increasing the light intensity up to 1,500 μmol m⁻² s⁻¹ could prompt microalgae growth and improve the nutrient removal efficiency (Tuantet et al., 2014).

TABLE 3 The performance of microalgae production in urine.

Microalgae	Cultivation media	Dilution	Biomass X_t , g L ⁻¹	Productivity β , g L ⁻¹ day ⁻¹	Lipids, g L ⁻¹	Protein/Fatty acid content, %	Supplements	Refs.
<i>C. vulgaris</i>	RHU	n.d./100 ^a	0.73/0.59VSS	0.08/0.06VSS	n.a.	n.a.	Trace elements	Jaatinen et al. (2016)
		25–300	0.48–0.60VSS	0.05–0.07VSS	n.a.	n.a.	–	
<i>C. sorokiniana</i>	RHU	6	1.8	n.a.	n.a.	n.a.	–	de Wilt et al. (2016)
			2.7	n.a.	n.a.	n.a.	With	
<i>D. abundans</i>	SHU	n.d.	5.5	n.a.	n.a.	n.a.	micropollutants	Piltz and Melkonian (2017)
	RHU	n.d.	n.a.	14.5	n.a.	n.a.	–	
<i>C. soroliniana</i>	RHU	2	n.a.	14.8	0.9–3.6	38–48/(16–25w/w)	Mg and P	Tuantet et al. (2014)
	SHU	2	7.5	n.a.	n.a.	n.a.	P	
<i>S. acuminatus</i>	RHU	20 and 15	0.34	n.a.	n.a.	n.a.	–	Chatterjee et al. (2019)
<i>C. vulgaris</i>	RHU	30	2.14	0.313	n.a.	n.a.	–	Nguyen et al. (2021)
<i>S. platensis</i>	RHU	120	0.81	n.a.	19.8	35.4	–	Chang et al. (2013)
	SHU		0.75/1.17/1.75	n.a.	17.2/17.5/17.9	36.2/56.4/60.2	–/100/200 mg L ⁻¹ CH ₃ COONa	
<i>S. platensis</i>	RHU/SHU	180	2.32/2.40	n.a.	20.43/17.58%	32.4/34.78	–	Feng and Wu (2006)
<i>C. soroliniana</i>	RHU	2	n.a.	9.3	16%–25% w/w	43%–53% w/w	Mg ²⁺	Tuantet et al. (2013)
<i>S. platensis</i>	SHU/RHU	n.d.	1.05/2.9–3.4	n.a.	n.a.	n.a.	–	Yang et al. (2008)
<i>C. sorokiniana</i>	Swine ^b	2	5.54	n.a.	n.a.	0.27 g L ⁻¹ day ⁻¹	–	Chen et al. (2020)
		2	8.08	n.a.	n.a.	0.272 g L ⁻¹ day ⁻¹	–	

^an.a. represents “not available”; n.d., no dilution.

^bSwine wastewater was listed for comparison.




FIGURE 4

Comparison of (A) nitrogen and (B) phosphorus removal by algal cultivation at different illumination/light intensities and cultivation time. The size of bubbles represents the percentage removal. Red circles: dilution >20, and blue circles: dilution <10. Data were achieved from the literature (Adamsson, 2000; Yang et al., 2008; Chang et al., 2013; Tuantet et al., 2013, 2014, 2019; Zhu et al., 2013; Zhang et al., 2014; de Wilt et al., 2016; Jaatinen et al., 2016; Piltz and Melkonian, 2017; Chatterjee et al., 2019; Chen et al., 2020; Nguyen et al., 2021).

Temperature change also influences the solubilization and volatilization of ammonia, thus leading to pH excursion. As shown in Table 2, a temperature between 30°C and 40°C is typically applied to the incubation because, for example, the optimal temperature for the growth of *S. platensis* is between 29°C and 32°C (Yang et al., 2008). Nevertheless, some microalgae can tolerate low temperatures; for example, *S. acuminatus* could grow in human urine even at 5°C with the

recovery of N and P achieving 52% and 38%, respectively, (Chatterjee et al., 2019).

Retention time

As for photobioreactor design and operation, biomass and hydraulic retention time (BRT and HRT) are two key parameters

(Nguyen et al., 2021). Results in Figure 4 indicate that BRT may have a positive relationship with nutrients removal from urine. In a PBR, BRT relates to biomass accumulation and thus determines the nutrient removal rates (Akerstrom et al., 2014). A short BRT (2–5 days) may not be sufficient to sustain the rapid growth of microalgae, which consequently limits the biomass production rate even when a high nitrogen uptake rate is obtained (Luo et al., 2017; Praveen et al., 2019). Likewise, the highest TP removal of 52.1% was achieved at a BRT of 7 days during incubation (Nguyen et al., 2021). It should be noted that a longer BRT may result in the deterioration of the settling/harvesting properties of the biomass (Wang et al., 2013; Ma et al., 2018a). In addition, a longer HRT resulting from an extended BRT would decrease the productivity of a PBR to treat human urine. Conversely, a short HRT leads to higher nutrient loads but compromises the removal of N and P. To address the limitations, membrane separation processes have been integrated with PBRs (MPBR) to achieve flexible control of BRT and HRT. High nutrient loads such as 90–110 mg-NL⁻¹ day⁻¹ and 5–6 mg-PL⁻¹ day⁻¹ have been used in MPBRs (Nguyen et al., 2021). In summary, the BRT and HRT should be set given the treatment efficiency and capital cost for bioreactor deployment. According to the study by Nguyen et al. (2021), a short BRT (7 days) and an extended HRT (>2 days) are thus suggested to capture nutrients from urine while minimizing the environmental impacts effectively.

Trace elements

Tuantet (2015) found that the algal growth was inhibited due to the exhaustion of trace elements within 24 h, highlighting the importance of trace elements in biomass production in diluted urine. As for the effect of dilution on microalgae growth, Jaatinen et al. (2016) reported that the highest biomass densities of 0.73 and 0.60 g L⁻¹ were obtained at 1:100 dilution of urine with and without the addition of trace elements. Moreover, *C. sorokiniana* showed the fastest growth rate in urine diluted 20 times with trace elements added (Tuantet et al., 2013).

Magnesium (Mg²⁺), iron (mainly in the form of Fe^{II}) and certain trace elements are present in urine at low concentrations (Tuantet et al., 2013). When urine is collected and stored, the formation of precipitates due to an increase in pH reduces the availability of these elements. Udert et al. (2003) demonstrated that the precipitation capacity of guano stone and octa calcium phosphate in urine reached 87% when the hydrolysis rate was 11%. As a result, the magnesium content in hydrolyzed urine (0.15–0.17 mg L⁻¹) could be significantly lower than in fresh urine (25.4 ± 17.0 mg L⁻¹; Zhang et al., 2014). Mg²⁺ plays a vital role in algal metabolism because it is essential for chlorophyll production (Sydney et al., 2010). The magnesium content in *Chlorella* sp. ranged from 0.36% to 0.80% of dry weight, and only 40 mg L⁻¹ dry biomass could be sustained at a 0.36% magnesium content (Borowitzka and Borowitzka, 1988). Therefore, magnesium supplementation is essential to promote microalgal growth in

hydrolyzed urine (Table 3; Tuantet et al., 2019). No significant difference was found between the specific growth rates of microalgae fed with hydrolyzed urine with additional Mg²⁺ ($\mu = 0.095\text{--}0.111\text{ h}^{-1}$) as compared to synthetic and fresh urine (Tuantet et al., 2013). Moreover, iron is also one of the most crucial trace metals involved in the enzymatic reactions of photosynthesis in photosystem I (PSI) and PSII (Cao et al., 2014). An increase in the iron concentration in the medium (1.2×10^{-2} mM) would elevate the biomass as well as lipid content of *C. vulgaris* (Liu Z.-Y. et al., 2008). Note that significant elements such as Cl also indispensably contribute to the photosynthesis of chlorophyll and affect the uptake of trace elements (Yang et al., 2008).

Inorganic/organic carbon source

Typically, microalgae production in human urine uses the internal inorganic carbon source of bicarbonate (HCO₃⁻) and/or exogenous sparged CO₂. Additional CO₂ can prompt the growth of microalgae. As shown in Table 2, the gas concentration (v/v) of extra CO₂ ranges from 1% to 20% because an overhigh CO₂ dose may cause acidification of the media. Nevertheless, field studies have shown that microalgae cultivation by using flue gasses can withstand a high CO₂ concentration of 40% (Pires et al., 2012).

Besides, microalgae can grow under mixotrophic conditions. Under autotrophic conditions, *S.platensis* fed with an inorganic carbon source (with ammonium or urea as the nitrogen source) demonstrated a yellowish-green appearance with relatively low protein content. At the same time, the biomass became green and difficult to settle down after adding an organic carbon source (Chang et al., 2013). Adding an organic carbon source could alleviate the inhibition effect of ammonium. For example, by adding 100 and 200 mg L⁻¹ sodium acetate (or glucose) to the synthetic urine (Table 3), the productivity of *S.platensis* was improved with the nitrogen and phosphorus removal increasing from 97% and 96.5% to ~100% and 98%, respectively (Chang et al., 2013). As for treating urea in human urine, adding an organic carbon source could also facilitate the removal of ammonia *via* biomass production. As such, introducing waste organic carbon sources (e.g., effluents from food plants) to microalgae cultivation in human urine can provide a valuable solution to increase nutrient recovery efficiency.

pH

Medium pH directly influences microalgae growth and determines the speciation of nutrients that may support or inhibit biomass production. As aforementioned, hydrolysis of urea in human urine produces HCO₃⁻ and ammonia while raising the solution pH (Adamsson, 2000; Zhang et al., 2013). Conversion between ammonia and ammonium is primarily determined by the solution pH ($pK_a = 9.25$; Zhang et al., 2018; He et al., 2022; Zhang

et al., 2022), and higher pH could facilitate the transformation of NH_4^+ to NH_3 (Figure 5). NH_3 is far more toxic than NH_4^+ because the transport of NH_4^+ involves the participation of transporters (Figure 5C; Källqvist and Svenson, 2003; Wang et al., 2019). Ammonia or free ammonia can reduce photosynthetic activity and directly shows toxicity to microalgae (Zhang et al., 2014). The photosynthetic rate of *Scenedesmus* was allegedly decreased by 50% of its maximum rate in the presence of free ammonia of 20 mg L^{-1} under basic conditions (Azov and Goldman, 1982), though different microalgae species have different tolerance to the pH-dependent toxicity of $\text{NH}_3/\text{NH}_4^+$ (Tao et al., 2017a). As mentioned above, a high pH level can lead to the precipitation of unchelated trace metals, thus inhibiting algal growth (Adamsson, 2000). To stabilize the solution pH and neutralize the alkalinity especially when human urine is directly used as the feed, sparging of CO_2 (or diluted CO_2) has been carried out. In addition to serving as an inorganic carbon source, the excessive CO_2 can buffer the pH ($\text{pK}_a(\text{H}_2\text{CO}_3/\text{HCO}_3^-) = 6.30$; Ma et al., 2018b; Figure 5B) and prevent the inhibition of free ammonia on algal growth (Tuantet et al., 2014).

With the absorption of ammonium in algal growth, the pH would decrease because of the production and accumulation of H^+ , which slows down the growth rate (Azov and Goldman, 1982). In a photobioreactor, when the medium pH drops from pH 6.8 to <4 during cultivation, the microalgae would be subject to the cessation of growth or even death (Hulatt et al., 2012; Jaatinen et al., 2016). *C. sorokiniana* has shown a high specific growth rate within the pH range from 4 to 7 (Tuantet et al., 2014). In addition,


consideration should be given to the source of human urine. For example, it has been reported that gender may influence the pH because the female urine demonstrated a more narrow pH window (7.1–7.9) as compared to that (5.7 and 8.0) of the male urine (Tuantet, 2015).

Perspectives and outlook

In this section, we discuss the challenges that should be addressed toward a broader application of microalgae production in urine. Important questions may include (i) the impacts of co-existing bacteria, and (ii) contamination by human metabolites. According to the literature, consideration should also be given to the genetic engineering that has been playing a more crucial role in increasing biomass/biofuel production.

Co-existing bacteria

When non-sterilized human urine is used as the feed, bacterial contamination of the cultivations very likely occurs, which leads to competition for the nutrients and lower conversion to algal biomass. While this problem in the early growth stage may be solved by sterilization of the inoculation medium, it was reported that a large variety of bacteria were detected from *C. vulgaris* cultures grown on both sterilized and non-sterilized media at an extended cultivation period (Jaatinen et al., 2016). Maintaining the culture composition



in the photoautotrophic mode (i.e., in the absence of organic carbon) may inhibit the competition from bacterial growth. Microalgal cells can regain dominance in the diverse community in 2 days when the organic carbon supply ceases (Zhang et al., 2014). Nevertheless, the autotrophic nitrifiers can adapt to fill a similar ecological niche compared to the microalgae though the biomass yield of ammonia-oxidizing bacteria is low (Ma et al., 2013a, 2015). In the symbiosis, a consortium of microalgae and nitrifying bacteria can decrease the need of expensive external aeration (Sun et al., 2020; Li et al., 2022). The photosynthetic oxygenation rate can drive the nitrification in urine with a volumetric nitrification rate of $67 \text{ mg NL}^{-1} \text{ day}^{-1}$, and a maximum biomass-specific photooxygenation rate of $160 \text{ mg O}_2 \text{ gVSS}^{-1} \text{ day}^{-1}$ (Muys et al., 2018).

In addition, the microalgae growth also leads to the secretion of extracellular organic matter that can be used by heterotrophic bacteria (Zhang et al., 2014). In turn, microalgae can convert nutrients into cellular components through photosynthesis and respiration. Currently, some single-cell microalgae such as *Chlamydomonas*, *Chlorella* and *Phormidium* are proven candidate for the formation of symbiosis suitable for waste treatment and facilitates the removal of N and P (Nguyen et al., 2020a). Inoculation of *Arthrospira platensis* with nitrated urine has been found to exhibit better growth and produce 62% more protein than untreated urine (Coppens et al., 2016). As for biofuel production, the biomass consisting of bacteria and microalgae may provide higher biogas production than pure microalgae (Jaatinen et al., 2016). For instance, 17%–24% higher methane yields ($376\text{--}403 \text{ ml-CH}_4\text{-g-VS}^{-1}$) were obtained from a mixture of microalgae (*C. vulgaris*) and bacteria (1%–10%) than the control that only contained microalgae (Lu et al., 2013). As such, the following studies to explore (i) the algal and bacterial inter-group competition and collaboration and (ii) the impacts of co-existing bacteria on biofuel conversion are required to advance the process performance.

Contamination by human metabolites

Source-separated urine contains about $60 \pm 30\%$ of drugs and lifestyle biomarkers consumed by humans (Monetti et al., 2022). Following intake, ~50% of pharmaceuticals do not change the chemical form, and are discharged with the intermediates as human metabolites (Lienert et al., 2007). Some human metabolites (e.g., conjugates of the antibiotic sulfamethoxazole, the anti-convulsant carbamazepine and the analgesic ibuprofen; Quinn et al., 2009; Ren et al., 2022a,b; Yang et al., 2022) have detrimental effects on the environment and may pose direct toxicity to microalgae. For instance, the anticonvulsant carbamazepine and the antidepressant fluoxetine form more toxic metabolites than their parent compounds (Verstraete et al., 1997; Jelic et al., 2015; Monetti et al., 2022). In contrast to the abundant studies of the contents of N, P and organic matter (Table 1) that influence microalgae growth and biomass production, there is little investigation of the micropollutants in urine involving the metabolism of microalgae. de Wilt et al. (2016) evaluated the

efficiency of microalgae *C. sorokiniana* to remove six spiked pharmaceuticals ($147 \pm 9 \mu\text{g L}^{-1}$ diclofenac, $317 \pm 33 \mu\text{g L}^{-1}$ ibuprofen, $337 \pm 23 \mu\text{g L}^{-1}$ paracetamol, $181 \pm 62 \mu\text{g L}^{-1}$ metoprolol, $117 \pm 17 \mu\text{g L}^{-1}$ carbamazepine and $202 \pm 30 \mu\text{g L}^{-1}$ trimethoprim). Results showed that 60%–100% of diclofenac, ibuprofen, paracetamol and metoprolol could be readily removed by photolysis and biodegradation while carbamazepine was refractory (removal <30%; de Wilt et al., 2016). While the presence of micropollutants at $100\text{--}300 \mu\text{g L}^{-1}$ did not inhibit microalgae (*C. sorokiniana*) growth, the deployment of pre-treatment technologies may be required at higher concentrations to prevent the pitfalls. Specific micropollutants can be removed by activated carbon, an effective absorbent for various organic and inorganic molecules because of the large surface area, porous structure and surface-bound groups (Yin et al., 2007). Activated carbon adsorption has been applied to eliminate antibiotics, beta-blockers, and nonsteroidal anti-inflammatory drugs from urine (Udert et al., 2016). Future work is essential to (i) assess the microalgae response to micropollutants at elevated concentrations, and (ii) develop cost-effective, reliable and environmentally benign processes to polish human urine under realistic conditions.

Genetic engineering

Essentially, the accumulation of neutral lipids by *Acutodesmus*, *Phaeodactylum*, *Dunaliella* and *Nannochloropsis* requires nutrient limitation or starvation, which can inhibit microalgal growth (Sun et al., 2018). While the acquisition of favorable and stable traits can be conducted *via* crossbreeding for crops (Armbrust, 1999; Chepurinov et al., 2008), this is not applicable to most microalgae that have some deficiency (Dismukes et al., 2008). To address the limitation, microalgae genetic engineering is considered as an optimal approach to solve this bottleneck. Direct or indirect genetic modification has been proposed as a means to improve the growth and lipid productivity of promising microalgal strains.

Genetic engineering can facilitate lipid accumulation without affecting the algal growth (Munoz et al., 2021), by modifying the single metabolic pathways including fatty acid synthesis metabolism, Kennedy pathway, polyunsaturated fatty acid and triacylglycerol metabolisms and fatty acid catabolism. For example, the synthesis of fatty acids requires a continuous supply of acetyl-CoA. Compared with wild type strains, the total lipid contents of *N. oceanica* and *Schizochytrium* sp. were increased by 36% and 11%, respectively, by employing the overexpress of the malonyl-CoA acyl carrier protein transacylase (Chen et al., 2017). In addition, commercial production of large-scale bulk of microalgae is still not feasible (Remmers et al., 2018). Genetic engineering may pave the way for increasing the photosynthetic rate to modulate the carbon flux toward lipids while maintaining high biomass production (Ajjawi et al., 2017). This strategy to prompt the yield of microalgae lipids may eventually make microalgal derivatives an effective means of commercial biofuels.

Conclusion

In conclusion, we present a comprehensive overview of the synthetic/human urine, microalgae species and photobioreactors that have been recently used in the algal production in urine. The standard matrices, including specific growth rate, biomass productivity, photosynthetic and harvesting efficiencies, and nutrients removal and recovery, have provided a platform for comparison among different studies. A summary of the critical operating factors is expected to facilitate our understanding of how the photobioreactors should be maintained to achieve high efficiencies. It is also recognized that the impacts of co-existing bacteria, contamination by human metabolites, and genetic engineering require continuing investigation toward a broader application of microalgae biomass production in urine.

Author contributions

YT: resourcing and writing—original draft preparation. ZL: conceptualization and resourcing. JuZ: reviewing and editing. JiZ: data collection. DH: writing—reviewing and editing. JM: supervision, writing—reviewing, and editing. All authors contributed to the article and approved the submitted version.

References

- Adamsson, M. (2000). Potential use of human urine by greenhouse culturing of microalgae (*Scenedesmus acuminatus*), zooplankton (*Daphnia magna*) and tomatoes (*Lycopersicon*). *Ecol. Eng.* 16, 243–254. doi: 10.1016/S0925-8574(00)00064-1
- Ajjawi, I., Verruto, J., Aquil, M., Soriaga, L. B., Coppersmith, J., Kwok, K., et al. (2017). Lipid production in *Nannochloropsis gaditana* is doubled by decreasing expression of a single transcriptional regulator. *Nat. Biotechnol.* 35, 647–652. doi: 10.1038/nbt.3865
- Akerstrom, A. M., Mortensen, L. M., Rusten, B., and Gislerod, H. R. (2014). Biomass production and nutrient removal by *Chlorella* sp. as affected by sludge liquor concentration. *J. Environ. Manag.* 144, 118–124. doi: 10.1016/j.jenvman.2014.05.015
- Armbrust, E. V. (1999). Identification of a new gene family expressed during the onset of sexual reproduction in the centric diatom *Thalassiosira weissflogii*. *Appl. Environ. Microbiol.* 65, 3121–3128. doi: 10.1128/AEM.65.7.3121-3128.1999
- Azov, Y., and Goldman, J. C. (1982). Free ammonia inhibition of algal photosynthesis in intensive cultures. *Appl. Environ. Microbiol.* 43, 735–739. doi: 10.1128/aem.43.4.735-739.1982
- Bahcegul, E., Tatli, E., Haykir, N. I., Apaydin, S., and Bakir, U. (2011). Selecting the right blood glucose monitor for the determination of glucose during the enzymatic hydrolysis of corn cob pretreated with different methods. *Bioresour. Technol.* 102, 9646–9652. doi: 10.1016/j.biortech.2011.07.116
- Behera, B., Patra, S., and Balasubramanian, P. (2020). Biological nutrient recovery from human urine by enriching mixed microalgal consortium for biodiesel production. *J. Environ. Manag.* 260:110111. doi: 10.1016/j.jenvman.2020.110111
- Belkin, S., and Boussiba, S. (1991). High internal pH conveys ammonia resistance in *Spirulina platensis*. *Bioresour. Technol.* 38, 167–169. doi: 10.1016/0960-8524(91)90149-E
- Boelee, N. C., Temmink, H., Janssen, M., Buisman, C. J., and Wijffels, R. H. (2011). Nitrogen and phosphorus removal from municipal wastewater effluent using microalgal biofilms. *Water Res.* 45, 5925–5933. doi: 10.1016/j.watres.2011.08.044
- Borowitzka, M. A., and Borowitzka, L. J. (1988). *Micro-algal biotechnology*. Cambridge University Press.
- Braune, S., Krüger-Genge, A., Kammerer, S., Jung, F., and Küpper, J. H. (2021). Phycocyanin from *arthropsira platensis* as potential anti-cancer drug: review of in vitro and in vivo studies. *Life* 11:91. doi: 10.3390/life11020091
- Cao, J., Yuan, H., Li, B., and Yang, J. (2014). Significance evaluation of the effects of environmental factors on the lipid accumulation of *Chlorella minutissima* UTEX 2341 under low-nutrition heterotrophic condition. *Bioresour. Technol.* 152, 177–184. doi: 10.1016/j.biortech.2013.10.084
- Chang, Y. Y., Wu, Z. C., Bian, L., Feng, D. L., and Leung, D. Y. C. (2013). Cultivation of *Spirulina platensis* for biomass production and nutrient removal from synthetic human urine. *Appl. Energy* 102, 427–431. doi: 10.1016/j.apenergy.2012.07.024
- Chatterjee, P., Granatier, M., Ramasamy, P., Kokko, M., Lakaniemi, A. M., and Rintala, J. (2019). Microalgae grow on source separated human urine in Nordic climate: outdoor pilot-scale cultivation. *J. Environ. Manag.* 237, 119–127. doi: 10.1016/j.jenvman.2019.02.074
- Chen, C. Y., Kuo, E. W., Nagarajan, D., Ho, S. H., Dong, C. D., Lee, D. J., et al. (2020). Cultivating *Chlorella sorokiniana* AK-1 with swine wastewater for simultaneous wastewater treatment and algal biomass production. *Bioresour. Technol.* 302:122814. doi: 10.1016/j.biortech.2020.122814
- Chen, J. W., Liu, W. J., Hu, D. X., Wang, X., Balamurugan, S., Alimujiang, A., et al. (2017). Identification of a malonyl CoA-acyl carrier protein transacylase and its regulatory role in fatty acid biosynthesis in oleaginous microalga *Nannochloropsis oceanica*. *Biotechnol. Appl. Biochem.* 64, 620–626. doi: 10.1002/bab.1531
- Cheng, H., Li, G., Han, Z., Li, J., and Wang, F. (2021). Evaluation of *Desmodesmus* sp. QL96 protein on nutritional value and its physiological activity. *Chin. J. Tropical Crops* 42:1440. doi: 10.3969/j.issn.1000-2561.2021.05.033
- Cheng, P., Osei-Wusu, D., Zhou, C., Wang, Y., Xu, Z., Chang, T., et al. (2020). The effects of refractory pollutants in swine wastewater on the growth of *Scenedesmus* sp. with biofilm attached culture. *Int. J. Phytoremediation* 22, 241–250. doi: 10.1080/15226514.2019.1658706
- Chepurinov, V. A., Mann, D. G., Von Dassow, P., Vanormelingen, P., Gillard, J., Inze, D., et al. (2008). In search of new tractable diatoms for experimental biology. *BioEssays* 30, 692–702. doi: 10.1002/bies.20773
- Coppens, J., Lindeboom, R., Muys, M., Coessens, W., Alloul, A., Meerbergen, K., et al. (2016). Nitrification and microalgae cultivation for two-stage biological nutrient valorization from source separated urine. *Bioresour. Technol.* 211, 41–50. doi: 10.1016/j.biortech.2016.03.001

Funding

This work was financially supported by the National Natural Science Foundation of China (52100030), the Guangdong Natural Science Funds for Distinguished Young Scholars (2022B1515020053) and the Guangzhou Science and Technology Project (202201010622).

Conflict of interest

The authors declare that the research was conducted in the absence of any commercial or financial relationships that could be construed as a potential conflict of interest.

Publisher's note

All claims expressed in this article are solely those of the authors and do not necessarily represent those of their affiliated organizations, or those of the publisher, the editors and the reviewers. Any product that may be evaluated in this article, or claim that may be made by its manufacturer, is not guaranteed or endorsed by the publisher.

- Cuaresma, M., Janssen, M., Vilchez, C., and Wijffels, R. H. (2009). Productivity of *Chlorella sorokiniana* in a short light-path (SLP) panel photobioreactor under high irradiance. *Bioeng. Technol.* 104, 352–359. doi: 10.1002/bit.22394
- Danesi, E. D. G., Rangel-Yagui, D. O., De Carvalho, J. C. M., and Sato, S. (2002). An investigation of effect of replacing nitrate by urea in the growth and production of chlorophyll by *Spirulina platensis*. *Biomass Bioenergy* 23, 261–269. doi: 10.1016/S0961-9534(02)00054-5
- Darienko, T., Rad-Menéndez, C., Campbell, C., and Pröschold, T. (2019). Are there any true marine *Chlorella* species? Molecular phylogenetic assessment and ecology of marine *Chlorella*-like organisms, including a description of *Droopiella* gen. nov. *Systematics and biodiversity* 17, 811–829. doi: 10.1080/14772000.2019.1690597
- de Wilt, A., Butkovskiy, A., Tuantet, K., Leal, L. H., Fernandes, T. V., Langenhoff, A., et al. (2016). Micropollutant removal in an algal treatment system fed with source separated wastewater streams. *J. Hazard. Mater.* 304, 84–92. doi: 10.1016/j.jhazmat.2015.10.033
- Detrell, G., Helisch, H., Keppler, J., Martin, J., and Henn, N. (2020). “Microalgae for combined air revitalization and biomass production for space applications,” in *From Biofiltration to Promising Options in Gaseous Fluxes Bioremediation*. eds. S. Gabriela and D. Éric (Elsevier Inc), 419–445.
- Disimukes, G. C., Carrieri, D., Bennette, N., Ananyev, G. M., and Posewitz, M. C. (2008). Aquatic phototrophs: efficient alternatives to land-based crops for biofuels. *Curr. Opin. Biotechnol.* 19, 235–240. doi: 10.1016/j.copbio.2008.05.007
- Feng, D. L., and Wu, Z. C. (2006). Culture of *Spirulina platensis* in human urine for biomass production and O(2) evolution. *J. Zhejiang Univ Sci B* 7, 34–37. doi: 10.1631/jzus.2006.B0034
- Gao, F., Li, C., Yang, Z.-H., Zeng, G.-M., Feng, L.-J., Liu, J.-Z., et al. (2016). Continuous microalgae cultivation in aquaculture wastewater by a membrane photobioreactor for biomass production and nutrients removal. *Ecol. Eng.* 92, 55–61. doi: 10.1016/j.ecoleng.2016.03.046
- Gao, F., Peng, Y.-Y., Li, C., Cui, W., Yang, Z.-H., and Zeng, G.-M. (2018). Coupled nutrient removal from secondary effluent and algal biomass production in membrane photobioreactor (MPBR): effect of HRT and long-term operation. *Chem. Eng. J.* 335, 169–175. doi: 10.1016/j.cej.2017.10.151
- Gòdia, F., Albiol, J., Montesinos, J. L., Pérez, J., Creus, N., Cabello, F., et al. (2002). MELISSA: a loop of interconnected bioreactors to develop life support in space. *J. Biotechnol.* 99, 319–330. doi: 10.1016/S0168-1656(02)00222-5
- Golder, D., Rana, S., Sarkar, D., and Jana, B. B. (2007). Human urine is an excellent liquid waste for the culture of fish food organism, *Moina micrura*. *Ecol. Eng.* 30, 326–332. doi: 10.1016/j.ecoleng.2007.04.002
- Gutierrez-Salmeán, G., Fabila-Castillo, L., and Chamorro-Cevallos, G. (2015). Nutritional and toxicological aspects of spirulina (*Arthrospira*). *Nutr. Hosp.* 32, 34–40. doi: 10.3305/nh.2015.32.1.9001
- He, C., Wang, J., Fu, L., Zhao, C., and Huo, J. (2022). Associative vs. dissociative mechanism: Electrocatalysis of nitric oxide to ammonia. *Chin. Chem. Lett.* 33, 1051–1057. doi: 10.1016/j.ccl.2021.09.009
- Holdmann, C., Schmid-Staiger, U., Hornstein, H., and Hirth, T. (2018). Keeping the light energy constant—cultivation of *Chlorella sorokiniana* at different specific light availabilities and different photoperiods. *Algal Res.* 29, 61–70. doi: 10.1016/j.algal.2017.11.005
- Hulatt, C. J., Lakaniemi, A.-M., Puhakka, J. A., and Thomas, D. N. (2012). Energy demands of nitrogen supply in mass cultivation of two commercially important microalgal species, *Chlorella vulgaris* and *Dunaliella tertiolecta*. *Bioenergy Res.* 5, 669–684. doi: 10.1007/s12155-011-9175-x
- Hydrobiology, F.A.C.C.O.T.I.O. (2013). *Spirulina platensis* [Online]. Available at: <http://algaebib.ac.cn/english/algaedetail.aspx?id=448> (Accessed October 4, 2022).
- Jaatinen, S., Lakaniemi, A. M., and Rintala, J. (2016). Use of diluted urine for cultivation of *Chlorella vulgaris*. *Environ. Technol.* 37, 1159–1170. doi: 10.1080/09593330.2015.1105300
- Jelic, A., Rodriguez-Mozaz, S., Barcelo, D., and Gutierrez, O. (2015). Impact of in-sewer transformation on 43 pharmaceuticals in a pressurized sewer under anaerobic conditions. *Water Res.* 68, 98–108. doi: 10.1016/j.watres.2014.09.033
- Källqvist, T., and Svensson, A. (2003). Assessment of ammonia toxicity in tests with the microalga, *Nephroselmis pyriformis*, Chlorophyta. *Water Res.* 37, 477–484. doi: 10.1016/S0043-1354(02)00361-5
- Karlson, B., Andreasson, A., Johansen, M., Karlberg, M., Loo, A., and Skjevik, A.-T., (2020). *Nordic Microalgae [online]*. World-Wide Electronic Publication. Available at: <http://nordicmicroalgae.org> (Accessed October 10 2022).
- Kim, J.-Y., and Kim, H.-W. (2017). Photoautotrophic microalgae screening for tertiary treatment of livestock wastewater and bioresource recovery. *Water* 9:192. doi: 10.3390/w9030192
- Kim, G. Y., Yun, Y. M., Shin, H. S., Kim, H. S., and Han, J. I. (2015). Scenedesmus-based treatment of nitrogen and phosphorus from effluent of anaerobic digester and bio-oil production. *Bioresour. Technol.* 196, 235–240. doi: 10.1016/j.biortech.2015.07.091
- Kinnunen, V., and Rintala, J. (2016). The effect of low-temperature pretreatment on the solubilization and biomethane potential of microalgae biomass grown in synthetic and wastewater media. *Bioresour. Technol.* 221, 78–84. doi: 10.1016/j.biortech.2016.09.017
- Lakaniemi, A. M., Intihar, V. M., Tuovinen, O. H., and Puhakka, J. A. (2012). Growth of *Chlorella vulgaris* and associated bacteria in photobioreactors. *Microb. Biotechnol.* 5, 69–78. doi: 10.1111/j.1751-7915.2011.00298.x
- Larsen, T. A., Riechmann, M. E., and Udert, K. M. (2021). State of the art of urine treatment technologies: a critical review. *Water Res. X* 13:100114. doi: 10.1016/j.wroa.2021.100114
- Li, J., Ou, R., Liao, H., Ma, J., Sun, L., Jin, Q., et al. (2022). Natural lighting enhancing the algae proliferation and nitrogen removal in membrane-aerated bacterial-algal biofilm reactor. *Sci. Total Environ.* 851:158063. doi: 10.1016/j.scitotenv.2022.158063
- Lienert, J., Burki, T., and Escher, B. I. (2007). Reducing micropollutants with source control: substance flow analysis of 212 pharmaceuticals in faeces and urine. *Water Sci. Technol.* 56, 87–96. doi: 10.2166/wst.2007.560
- Liu, Z.-Y., Wang, G.-C., and Zhou, B.-C. (2008). Effect of iron on growth and lipid accumulation in *Chlorella vulgaris*. *Bioresour. Technol.* 99, 4717–4722. doi: 10.1016/j.biortech.2007.09.073
- Liu, Z., Zhao, Q., Wang, K., Lee, D., Qiu, W., and Wang, J. (2008). Urea hydrolysis and recovery of nitrogen and phosphorous as MAP from stale human urine. *J. Environ. Sci.* 20, 1018–1024. doi: 10.1016/S1001-0742(08)62202-0
- Lu, F., Ji, J., Shao, L., and He, P. (2013). Bacterial bioaugmentation for improving methane and hydrogen production from microalgae. *Biotechnol. Biofuels* 6:92. doi: 10.1186/1754-6834-6-92
- Luo, Y., Le-Clech, P., and Henderson, R. K. (2017). Simultaneous microalgae cultivation and wastewater treatment in submerged membrane photobioreactors: a review. *Algal Res.* 24, 425–437. doi: 10.1016/j.algal.2016.10.026
- Ma, J., Dai, R., Chen, M., Khan, S. J., and Wang, Z. (2018a). Applications of membrane bioreactors for water reclamation: micropollutant removal, mechanisms and perspectives. *Bioresour. Technol.* 269, 532–543. doi: 10.1016/j.biortech.2018.08.121
- Ma, J., He, C., He, D., Zhang, C., and Waite, T. D. (2018b). Analysis of capacitive and electrocatalytic contributions to water desalination by flow-electrode CDI. *Water Res.* 144, 296–303. doi: 10.1016/j.watres.2018.07.049
- Ma, J., Wang, Z., He, D., Li, Y., and Wu, Z. (2015). Long-term investigation of a novel electrochemical membrane bioreactor for low-strength municipal wastewater treatment. *Water Res.* 78, 98–110. doi: 10.1016/j.watres.2015.03.033
- Ma, J., Wang, Z., Yang, Y., Mei, X., and Wu, Z. (2013a). Correlating microbial community structure and composition with aeration intensity in submerged membrane bioreactors by 454 high-throughput pyrosequencing. *Water Res.* 47, 859–869. doi: 10.1016/j.watres.2012.11.013
- Ma, J., Wang, Z., Zhang, J., Waite, T. D., and Wu, Z. (2017). Cost-effective *Chlorella* biomass production from dilute wastewater using a novel photosynthetic microbial fuel cell (PMFC). *Water Res.* 108, 356–364. doi: 10.1016/j.watres.2016.11.016
- Ma, J., Wang, Z., Zou, X., Feng, J., and Wu, Z. (2013b). Microbial communities in an anaerobic dynamic membrane bioreactor (AnDMMBR) for municipal wastewater treatment: comparison of bulk sludge and cake layer. *Process Biochem.* 48, 510–516. doi: 10.1016/j.procbio.2013.02.003
- Maurer, M., Schwegler, P., and Larsen, T. A. (2003). Nutrients in urine: energetic aspects of removal and recovery. *Water Sci. Technol.* 48, 37–46. doi: 10.2166/wst.2003.0011
- Monetti, J., Nieradzki, L., Freguia, S., Choi, P. M., O’Brien, J. W., Thomas, K. V., et al. (2022). Urea hydrolysis and long-term storage of source-separated urine for reuse as fertilizer is insufficient for the removal of anthropogenic micropollutants. *Water Res.* 222:118891. doi: 10.1016/j.watres.2022.118891
- Moras Junior, W. G., Gorgich, M., Corrêa, P. S., Martins, A. A., Mata, T. M., and Caetano, N. S. (2020). Microalgae for biotechnological applications: cultivation, harvesting and biomass processing. *Aquaculture* 528:735562. doi: 10.1016/j.aquaculture.2020.735562
- Munoz, C. F., Sudfeld, C., Naduthodi, M. I. S., Weusthuis, R. A., Barbosa, M. J., Wijffels, R. H., et al. (2021). Genetic engineering of microalgae for enhanced lipid production. *Biotechnol. Adv.* 52:107836. doi: 10.1016/j.biotechadv.2021.107836
- Muys, M., Coppens, J., Boon, N., and Vlaeminck, S. E. (2018). Photosynthetic oxygenation for urine nitrification. *Water Sci. Technol.* 78, 183–194. doi: 10.2166/wst.2018.200
- Nazari, S., Zinatizadeh, A. A., Mirghorayshi, M., and Van Loosdrecht, M. C. M. (2020). Waste or gold? Bioelectrochemical resource recovery in source-separated urine. *Trends Biotechnol.* 38, 990–1006. doi: 10.1016/j.tibtech.2020.03.007
- Nguyen, T.-T., Bui, X.-T., Ngo, H. H., Nguyen, T.-T.-D., Nguyen, K.-Q., Nguyen, H.-H., et al. (2021). Nutrient recovery and microalgae biomass production from urine by membrane photobioreactor at low biomass retention times. *Sci. Total Environ.* 785:147423. doi: 10.1016/j.scitotenv.2021.147423

- Nguyen, T.-T., Lee, C., Field, R. W., and Kim, I. S. (2020a). Insight into organic fouling behavior in polyamide thin-film composite forward osmosis membrane: critical flux and its impact on the economics of water reclamation. *J. Membr. Sci.* 606:118118. doi: 10.1016/j.memsci.2020.118118
- Nguyen, T. T., Nguyen, T. T., An Binh, Q., Bui, X. T., Ngo, H. H., Vo, H. N. P., et al. (2020b). Co-culture of microalgae-activated sludge for wastewater treatment and biomass production: exploring their role under different inoculation ratios. *Bioresour. Technol.* 314:123754. doi: 10.1016/j.biortech.2020.123754
- Organisms, C. C. O. A. (2020). *Chlorella sorokiniana* [Online]. Culture Collection of Autotrophic Organisms. Available at: <https://ccala.butbn.cas.cz/en/chlorella-sorokiniana-shihira-et-krauss> (Accessed October 4, 2022).
- Pawar, S. B. (2016). Process engineering aspects of vertical column Photobioreactors for mass production of microalgae. *ChemBioEng Reviews* 3, 101–115. doi: 10.1002/cben.201600003
- Piltz, B., and Melkonian, M. (2017). Immobilized microalgae for nutrient recovery from source-separated human urine. *J. Appl. Phycol.* 30, 421–429. doi: 10.1007/s10811-017-1266-4
- Pires, J. C. M., Alvim-Ferraz, M. C. M., Martins, F. G., and Simões, M. (2012). Carbon dioxide capture from flue gases using microalgae: engineering aspects and biorefinery concept. *Renew. Sust. Energ. Rev.* 16, 3043–3053. doi: 10.1016/j.rser.2012.02.055
- Porra, R. J., Thompson, W. A., and Kriedemann, P. E. (1989). Determination of accurate extinction coefficients and simultaneous equations for assaying chlorophylls a and b extracted with four different solvents: verification of the concentration of chlorophyll standards by atomic absorption spectroscopy. *Biochimica et Biophysica Acta (BBA) - Bioenergetics* 975, 384–394. doi: 10.1016/S0005-2728(89)80347-0
- Posadas, E., Morales, M. D. M., Gomez, C., Acien, F. G., and Muñoz, R. (2015). Influence of pH and CO₂ source on the performance of microalgae-based secondary domestic wastewater treatment in outdoors pilot raceways. *Chem. Eng. J.* 265, 239–248. doi: 10.1016/j.cej.2014.12.059
- Praveen, P., Xiao, W., Lamba, B., and Loh, K.-C. (2019). Low-retention operation to enhance biomass productivity in an algal membrane photobioreactor. *Algal Res.* 40:101487. doi: 10.1016/j.algal.2019.101487
- Quinn, B., Gagné, F., and Blaise, C. (2009). Evaluation of the acute, chronic and teratogenic effects of a mixture of eleven pharmaceuticals on the cnidarian, *Hydra attenuata*. *Sci. Total Environ.* 407, 1072–1079. doi: 10.1016/j.scitotenv.2008.10.022
- Raeisossadati, M., Moheimani, N. R., and Parlevliet, D. (2020). Red luminescent solar concentrators to enhance *Scenedesmus* sp. biomass productivity. *Algal Res.* 45:101771. doi: 10.1016/j.algal.2019.101771
- Remmers, I. M., Wijffels, R. H., Barbosa, M. J., and Lamers, P. P. (2018). Can we approach theoretical lipid yields in microalgae? *Trends Biotechnol.* 36, 265–276. doi: 10.1016/j.tibtech.2017.10.020
- Ren, L., Chen, M., Ma, J., Li, Y., and Wang, Z. (2022a). Pd–O₂ interaction and singlet oxygen formation in a novel reactive electrochemical membrane for ultrafast sulfamethoxazole oxidation. *Chem. Eng. J.* 428:131194. doi: 10.1016/j.cej.2021.131194
- Ren, L., Ma, J., Chen, M., Qiao, Y., Dai, R., Li, X., et al. (2022b). Recent advances in electrocatalytic membrane for the removal of micropollutants from water and wastewater. *iScience* 25:104342. doi: 10.1016/j.isci.2022.104342
- Revellame, E. D., Aguda, R., Chistoserdov, A., Fortela, D. L., Hernandez, R. A., and Zappi, M. E. (2021). Microalgae cultivation for space exploration: assessing the potential for a new generation of waste to human life-support system for long duration space travel and planetary human habitation. *Algal Res.* 55:102258. doi: 10.1016/j.algal.2021.102258
- Rezvani, S., Saadaoui, I., Al Jabri, H., and Moheimani, N. R. (2022). Techno-economic modelling of high-value metabolites and secondary products from microalgae cultivated in closed photobioreactors with supplementary lighting. *Algal Res.* 65:102733. doi: 10.1016/j.algal.2022.102733
- Rodushkin, I., and Ödman, F. (2001). Application of inductively coupled plasma sector field mass spectrometry for elemental analysis of urine. *J. Trace Elem. Med. Biol.* 14, 241–247. doi: 10.1016/S0946-672X(01)80010-9
- Schuler, J. F., Diller, V. M., and Kersten, H. J. (1953). Preferential assimilation of ammonium ion by *Chlorella vulgaris*. *Plant Physiol.* 28, 299–303. doi: 10.1104/pp.28.2.299
- Singh, P., Guldhe, A., Kumari, S., Rawat, I., and Bux, F. (2015). Investigation of combined effect of nitrogen, phosphorus and iron on lipid productivity of microalgae *Ankistrodesmus falcatus* KJ671624 using response surface methodology. *Biochem. Eng. J.* 94, 22–29. doi: 10.1016/j.bej.2014.10.019
- Soares, F. R., Martins, G., and Seo, E. S. (2013). An assessment of the economic aspects of CO₂ sequestration in a route for biodiesel production from microalgae. *Environ. Technol.* 34, 1777–1781. doi: 10.1080/09593330.2013.816784
- Song, J., Wang, X., Ma, J., Wang, X., Wang, J., Xia, S., et al. (2018). Removal of *Microcystis aeruginosa* and microcystin-LR using a graphitic-C₃N₄/TiO₂ floating photocatalyst under visible light irradiation. *Chem. Eng. J.* 348, 380–388. doi: 10.1016/j.cej.2018.04.182
- Sun, L., Ma, J., Li, L., Tian, Y., Zhang, Z., Liao, H., et al. (2020). Exploring the essential factors of performance improvement in sludge membrane bioreactor technology coupled with symbiotic algae. *Water Res.* 181:115843. doi: 10.1016/j.watres.2020.115843
- Sun, H., Zhao, W., Mao, X., Li, Y., Wu, T., and Chen, F. (2018). High-value biomass from microalgae production platforms: strategies and progress based on carbon metabolism and energy conversion. *Biotechnol. Biofuels* 11:227. doi: 10.1186/s13068-018-1225-6
- Sydney, E. B., Sturm, W., De Carvalho, J. C., Thomaz-Soccol, V., Larroche, C., Pandey, A., et al. (2010). Potential carbon dioxide fixation by industrially important microalgae. *Bioresour. Technol.* 101, 5892–5896. doi: 10.1016/j.biortech.2010.02.088
- Tao, R., Kinnunen, V., Praveenkumar, R., Lakaniemi, A. M., and Rintala, J. A. (2017a). Comparison of *Scenedesmus acuminatus* and *Chlorella vulgaris* cultivation in liquid digestates from anaerobic digestion of pulp and paper industry and municipal wastewater treatment sludge. *J. Appl. Phycol.* 29, 2845–2856. doi: 10.1007/s10811-017-1175-6
- Tao, R., Lakaniemi, A. M., and Rintala, J. A. (2017b). Cultivation of *Scenedesmus acuminatus* in different liquid digestates from anaerobic digestion of pulp and paper industry biosludge. *Bioresour. Technol.* 245, 706–713. doi: 10.1016/j.biortech.2017.08.218
- Tuantet, K. (2015). *Microalgae Cultivation for Nutrient Recovery from Human Urine*. PhD. Wageningen, NL: Wageningen University.
- Tuantet, K., Janssen, M., Temmink, H., Zeeman, G., Wijffels, R. H., and Buisman, C. J. N. (2013). Microalgae growth on concentrated human urine. *J. Appl. Phycol.* 26, 287–297. doi: 10.1007/s10811-013-0108-2
- Tuantet, K., Temmink, H., Zeeman, G., Janssen, M., Wijffels, R. H., and Buisman, C. J. N. (2014). Nutrient removal and microalgal biomass production on urine in a short light-path photobioreactor. *Water Res.* 55, 162–174. doi: 10.1016/j.watres.2014.02.027
- Tuantet, K., Temmink, H., Zeeman, G., Wijffels, R. H., Buisman, C. J. N., and Janssen, M. (2019). Optimization of algae production on urine. *Algal Res.* 44:101667. doi: 10.1016/j.algal.2019.101667
- Udert, K. M., Buckley, C. A., Wächter, M., Mcardell, C. S., Kohn, T., Strande, L., et al. (2016). Technologies for the treatment of source-separated urine in the eThekweni municipality. *Water SA* 41, 2571–2582. doi: 10.4314/wsa.v41i2.06
- Udert, K. M., Larsen, T. A., Biebow, M., and Gujer, W. (2003). Urea hydrolysis and precipitation dynamics in a urine-collecting system. *Water Res.* 37, 2571–2582. doi: 10.1016/S0043-1354(03)00065-4
- Unpaprom, Y., Tipnee, S., and Rameshprabu, R. (2015). Biodiesel from green alga *Scenedesmus acuminatus*. *Int. J. Sustainable Green Energy* 4, 1–6. doi: 10.11648/j.ijrse.2015040101.11
- Verstraete, W., Tanghe, T., and Janssens, I. (1997). Micropollutants: a bottleneck in sustainable wastewater treatment. *Water Sci. Technol.* 35, 13–26. doi: 10.2166/wst.1997.0349
- Vilchez, C., and Vega, J. (1995). Nitrite uptake by immobilized *Chlamydomonas reinhardtii* cells growing in airlift reactors. *Enzym. Microb. Technol.* 17, 386–390. doi: 10.1016/0141-0229(94)00037-R
- Wang, H., Wang, X., Ma, J., Xia, P., and Zhao, J. (2017). Removal of cadmium (II) from aqueous solution: a comparative study of raw attapulgite clay and a reusable waste-struvite/attapulgite obtained from nutrient-rich wastewater. *J. Hazard. Mater.* 329, 66–76. doi: 10.1016/j.jhazmat.2017.01.025
- Wang, Z., Yu, H., Ma, J., Zheng, X., and Wu, Z. (2013). Recent advances in membrane bio-technologies for sludge reduction and treatment. *Biotechnol. Adv.* 31, 1187–1199. doi: 10.1016/j.biotechadv.2013.02.004
- Wang, J., Zhou, W., Chen, H., Zhan, J., He, C., and Wang, Q. (2019). Ammonium nitrogen tolerant *Chlorella* strain screening and its damaging effects on photosynthesis. *Front. Microbiol.* 9:3250. doi: 10.3389/fmicb.2018.03250
- Wilsenach, J. A., Schuurbiens, C. A., and Van Loosdrecht, M. C. (2007). Phosphate and potassium recovery from source separated urine through struvite precipitation. *Water Res.* 41, 458–466. doi: 10.1016/j.watres.2006.10.014
- Wilsenach, J. A., and Van Loosdrecht, M. C. (2006). Integration of processes to treat wastewater and source-separated urine. *J. Environ. Eng.* 132, 331–341. doi: 10.1061/(ASCE)0733-9372(2006)132:3(331)
- Yang, K., Lin, H., Feng, X., Jiang, J., Ma, J., and Yang, Z. (2022). Energy-efficient removal of trace antibiotics from low-conductivity water using a TiO₂ reactive electrochemical ceramic membrane: matrix effects and implications for byproduct formation. *Water Res.* 224:119047. doi: 10.1016/j.watres.2022.119047
- Yang, C., Liu, H., Li, M., Yu, C., and Yu, G. (2008). Treating urine by *Spirulina platensis*. *Acta Astronaut.* 63, 1049–1054. doi: 10.1016/j.actaastro.2008.03.008

- Yang, J., Xu, M., Zhang, X., Hu, Q., Sommerfeld, M., and Chen, Y. (2011). Life-cycle analysis on biodiesel production from microalgae: water footprint and nutrients balance. *Bioresour. Technol.* 102, 159–165. doi: 10.1016/j.biortech.2010.07.017
- Yin, C., Aroua, M., and Daud, W. (2007). Review of modifications of activated carbon for enhancing contaminant uptakes from aqueous solutions. *Sep. Purif. Technol.* 52, 403–415. doi: 10.1016/j.seppur.2006.06.009
- Yuan, D., Liu, J., Wang, H., Hu, Q., and Gong, Y. (2022). Biodiversity and seasonal variation of microzooplankton contaminating pilot-scale cultures of *Chlorella sorokiniana*. *Algal Res.* 64:102722. doi: 10.1016/j.algal.2022.102722
- Zhang, J., Giannis, A., Chang, V. W., Ng, B. J., and Wang, J. Y. (2013). Adaptation of urine source separation in tropical cities: process optimization and odor mitigation. *J. Air Waste Manag. Assoc.* 63, 472–481. doi: 10.1080/10962247.2013.763306
- Zhang, S., Lim, C. Y., Chen, C. L., Liu, H., and Wang, J. Y. (2014). Urban nutrient recovery from fresh human urine through cultivation of *Chlorella sorokiniana*. *J. Environ. Manag.* 145, 129–136. doi: 10.1016/j.jenvman.2014.06.013
- Zhang, C., Ma, J., He, D., and Waite, T. D. (2018). Capacitive membrane stripping for ammonia recovery (CapAmm) from dilute wastewaters. *Environ. Sci. Technol. Lett.* 5, 43–49. doi: 10.1021/acs.estlett.7b00534
- Zhang, D., Yang, S., Fang, X., Li, H., Chen, X., and Yan, D. (2022). In situ localization of BiVO₄ onto two-dimensional MXene promoting photoelectrochemical nitrogen reduction to ammonia. *Chin. Chem. Lett.* 33, 4669–4674. doi: 10.1016/j.ccl.2022.02.001
- Zhu, L., Wang, Z., Shu, Q., Takala, J., Hiltunen, E., Feng, P., et al. (2013). Nutrient removal and biodiesel production by integration of freshwater algae cultivation with piggery wastewater treatment. *Water Res.* 47, 4294–4302. doi: 10.1016/j.watres.2013.05.004
- Zittelli, G. C., Rodolfi, L., Bassi, N., Biondi, N., and Tredici, M. R. (2013). “Photobioreactors for microalgal biofuel production,” in *Algae for Biofuels and Energy*. eds. A. B. Michael and R. M. Navid (Springer Dordrecht), 115–131.

Glossary

ATP	Adenosine triphosphate
BRT	Biomass retention time
GOGAT	Glutamate synthase
GS	Glutamine synthase
HRT	Hydraulic retention time
MF	Microfiltration
MPBR	Membrane photobioreactor
OD	Optical density
OEC	Oxygen-evolving complex
PBR	Photobioreactor
PSI	Photosystem I
PSII	Photosystem II
PSBR	Porous substrate photobioreactors
SVR	Surface area to volume ratio
TN	Total nitrogen
TP	Total phosphorus

Symbol

Symbol	Entity	Unit
P_{area}	Area productivity	$\text{g m}^{-2} \text{day}^{-1}$
I_{phn}	Average light intensity	$\mu\text{mol}_{\text{ph}} \text{m}^{-2} \cdot \text{s}^{-1}$
X	Biomass concentration	g L^{-1}
X_{R}	Biomass concentration in the recovered volume	g L^{-1}
BRT	Biomass retention time	day
β	Biomass productivity	$\text{g L}^{-1} \text{day}^{-1}$
Chl a	Chlorophyll a concentration	mg L^{-1}
$I_{\text{phn}24}$	Daily integral light intensity	$\text{mol}_{\text{ph}} \cdot \text{m}^{-2} \cdot \text{day}^{-1}$
D	Dilution rate	h^{-1}
η	Harvesting efficiency	%
HRT	Hydraulic retention time	day
q	Liquid flow	L day^{-1}
C_{N}	Nitrogen concentrations	mg L^{-1}
N	OD of a predetermined wavelength	abs
p_{N}	Percentage removal of nitrogen	%
Y_{ph}	Photosynthetic efficiency	$\text{g mol}_{\text{ph}}^{-1}$
A_{r}	Reactor surface area	m^2
r_{N}	Removal rate of nitrogen	$\text{mg L}^{-1} \text{day}^{-1}$
μ	Specific growth rate	h^{-1}
SVR	Surface to volume ratio	m^{-1}
t	Time	day (or h)
V_{R}	Volume of the recovered solution	L