Check for updates

Corrigendum: Visual expertise modulates resting-state brain network dynamics in radiologists: a degree centrality analysis

Hongmei Wang[1,2†], Renhuan Yao[3†], Xiaoyan Zhang[4], Chao Chen[5], Jia Wu[6], Minghao Dong[4,7]* and Chenwang Jin[1]*

[1]Department of Radiology, First Affiliated Hospital of Xi'an, Jiaotong University, Xi'an, China, [2]Department of Medical Imaging, Inner Mongolia People's Hospital, Hohhot, China, [3]Department of Nuclear Medicine, Inner Mongolia People's Hospital, Hohhot, China, [4]Engineering Research Center of Molecular and Neuro Imaging of Ministry of Education, School of Life Science and Technology, Xidian University, Xi'an, China, [5]PLA Funding Payment Center, Beijing, China, [6]School of Foreign Languages, Northwestern Polytechnical University, Xi'an, Shaanxi, China, [7]Xi'an Key Laboratory of Intelligent Sensing and Regulation of Trans-Scale Life Information, School of Life Science and Technology, Xidian University, Xi'an, China

A corrigendum on

Visual expertise modulates resting-state brain network dynamics in radiologists: a degree centrality analysis

by Wang, H., Yao, R., Zhang, X., Chen, C., Wu, J., Dong, M., and Jin, C. (2023). *Front. Neurosci.* 17:1152619. doi: 10.3389/fnins.2023.1152619

In the published article, there was an error in the legend for Figure 1 as published, G, H was incorrectly written as D–H.

The corrected legend appears below.

The pipeline of the rs-MRI data analysis. **(A–C)** The resting-state MRI data were collected and preprocessed following procedures described in the Methods. Then, the DC for each voxel was calculated and used for future feature selection. **(D–F)** Feature selection. Two-step feature selection was performed and the first level used a two-sample approach to perform the regional average feature. Then, RFE-SVM modeling with LOOCV was employed to search for the most remarkable features between groups. **(G, H)** SVM modeling. Reliable SVM classification results and the brain areas with robust differences in DC values between groups were obtained to reflect the alteration of dynamics in the whole-brain network. rs-MRI, resting-state MRI; fMRI, functional magnetic resonance imaging; DC, degree centrality; RFE-SVM, recursive feature elimination-support vector machine; SVM, support vector machine; LOOCV, leave-one-out cross-validation.

The authors apologize for this error and state that this does not change the scientific conclusions of the article in any way. The original article has been updated.

Publisher's note

All claims expressed in this article are solely those of the authors and do not necessarily represent those of their affiliated organizations, or those of the publisher, the editors and the reviewers. Any product that may be evaluated in this article, or claim that may be made by its manufacturer, is not guaranteed or endorsed by the publisher.