



Scaling of Laser Fusion Experiments for DD-Neutron Yield

Josef Krása^{1*} and Daniel Klír²

¹ Institute of Physics of the Czech Academy of Sciences, Prague, Czechia, ² Faculty of Electrical Engineering, Czech Technical University in Prague, Prague, Czechia

Yields of neutrons produced in various laser fusion experiments conducted in recent decades are compared with each other. It has surprisingly been found that there is a possibility to make an overall elucidation of the variance in the number of neutrons produced in the various experiments. The common method is based on definition of the energy conversion efficiency as a ratio between the energy carried out by neutrons produced through the fusion reaction and the input energy given by laser energy, E, focused on a target. The neutron-yield – laser-energy (Y-E) diagram is the basic chart used to interpret the spread of experimental data in terms of the experimental efficiency of the laser-matter interaction. Experiments carried out using a single laser system show that laser energy dependence of the yield can be well-characterized by a power law, $Y = QE^{\alpha}$, where Q is the parameter reflecting possible dependence on the pulse duration, laser intensity, laser contrast ratio, focal geometry, target structure, etc. [1, 2]. Sorting the values of the neutron yields obtained in various experiments shows that the power law $Y = Q E^{1.65}$ is suitable to determine lines in the Y-E diagram each of them, where the value of Q is associated with quality of experimental conditions [3]. This sorting shows the order-of-magnitude differences in yields found in various experiments, which can be characterized by the value of the parameter Q. Due to the easy feasibility and the large number of DD fusion experiments performed, the overall Y-E diagram gives a chance to identify suitable laser systems for effective DD fusion experiments. It can, therefore, be assumed that some of the conclusions of these experiments could also be applied to the experimental arrangement suitable for optimizing p¹¹B fusion.

Keywords: laser-plasma interactions, DD neutron yield scaling, DT neutron yield scaling, preplasma effect, hydrogen-boron fusion

INTRODUCTION

Many efforts have been devoted to optimizing the heating of fusion targets by laser pulses to initiate different fusion reactions producing e.g., neutrons and alpha particles through fusion DD, DT and $p^{11}B$ reactions that carry released energy [4–6]. One of the important objectives for developing a usable fusion energy source is just to find an effective way to enhance the laser energy coupling to the target in the context of inertial confinement fusion research [7]. On the other hand, plasma as a source of fusion neutrons produced by the reaction, $D + D \rightarrow He^3 + n$, may not only be produced by large laser facilities, but also by small laser devices. If the plasma is produced by laser pulses over the energy range from millijoules to dozens of kilojoules, then fusion neutrons are released from beam fusion and thermal fusion initiated by fast deuterons ($E_D > 20$ keV). A number of different experiments have shown that the value of neutron yield corresponding to this laser energy range varies from a few neutrons to trillions per laser shot.

OPEN ACCESS

Edited by:

Noaz Nissim, Soreq Nuclear Research Center, Israel

Reviewed by:

Aldo Bonasera, Laboratori Nazionali del Sud (INFN), Italy Claude Deutsch, Université de Paris, France

> ***Correspondence:** Josef Krása krasa@fzu.cz

Specialty section:

This article was submitted to Interdisciplinary Physics, a section of the journal Frontiers in Physics

Received: 25 March 2020 Accepted: 06 July 2020 Published: 03 September 2020

Citation:

Krása J and Klír D (2020) Scaling of Laser Fusion Experiments for DD-Neutron Yield. Front. Phys. 8:310. doi: 10.3389/fphy.2020.00310

1

Analysis of a wider range of experimental data from different research groups around the world have made it possible to obtain scaling laws, especially for certain types of experiments. The scaling properties are generally attributed to the laser power dependence, where the reaction rate, the density of the plasma and the projected range of the plasma particle in the target medium play a decisive role. However, given the different conditions under which laser plasma experiments are performed, it is useful to sort and compare the results of different fusion experiments based on the dependence of neutron yield on a wide range of laser energy [8, 9]. The large scatter of values in the publications presented so far indicates that laser parameters such as pulse energy, pulse duration and maximum intensity do not fully determine the fusion yield. Thus, fusion yield also depends on other factors affecting acceleration of ions, such as laser pulse shape, laser contrast ratio, focal geometry, target structure, pre-plasma formation, as well as non-linear processes occurring during the laser-plasma interaction. Despite the large number of parameters and processes that affect fusion yield, the experimentally observed dependence of neutron yield on laser energy appears suitable for finding the optimal experimental conditions required for practical use.

The laser energy dependence of the fusion yield has been characterized by a power law dependence, $Y = QE^{\alpha}$, on laser energy E, where Q is the parameter reflecting the processes occurring in such plasmas, as mentioned above [1, 2]. The experiment dealing only with fusion neutron yields from explosions of deuterium clusters irradiated with a 100-TW laser shown that the value of α can range from 1 to 2.3 and Q from 1,430 to 13,200, as reported in [2, 10, 11]. The first comparison of different experiments on deuterated solid targets showed that a typical fusion experiment can be included in the group of experiments where $Y(E) = 2,000 \times E^{1.65}$ [3]. The $Y = QE^{1.6}$ dependence was also used in Ref. [12] to indicate a similar trend. In this paper, we will report more experimental data supporting this trend in yield increasing as a function of laser energy for deuterated plasma. The dependence of Q on other parameters that together determine the position of the yield value in the Y-E diagram can be considered as a measure of the efficiency of the laser-matter interaction applied.

Y-E DIAGRAMS

To measure the fusion yield ranging from over roughly 12 orders of magnitude, from the lowest yields of a few DD neutrons per laser shot up to 10^{12} [13, 14], various calibrated low/high yield detection systems consisting of e.g., time-of-flight scintillation neutron detectors, nuclear track detectors, bubble and thermoluminescent dosimeters, and activation detectors are used. The total neutron yield into the solid angle of 4π steradian per laser shot is determined assuming that the neutrons are emitted isotropically although there is evidence that the emission from the plasma may not be perfectly isotropic. In addition, the spatial and energy distribution of neutrons is affected by neutron scattering through the passage of the interaction vessel [1, 15, 16]. Regardless of inaccuracies in total neutron yield determination



systems, data from References [1–3, 10, 14, 17–35]. Pitcher-catcher configurations are not displayed. In the case of anisotropic neutron emission, equivalent 4π neutron yields were calculated from peak neutron fluence.

and differences in a number of parameters determining laser interaction with target, neutron yield generally increases with increasing energy deposited by the laser on target, as **Figure 1**. The data presented are collected from a series of experiments dedicated to the interaction of fs-ns laser pulses with deuterated targets of various configurations, such as solid planar target, spherical target, cryogenically cooled target, clusters etc. [1– 3, 10–12, 17–35]. Despite the large dispersion, these data show an increasing dependence of the neutron yield on laser energy. At the center of the data set, there is a large scattering of the neutron yield values: The yield ranges from 10⁵ to 10⁹ neutrons at deposited energy of 15 J. The horizontal-oriented line shows that the yield of 1×10^7 neutrons was achieved with both a high laser energy of 4,500 J and a low energy of 1 J. The 1 J-energy was clearly very effectively coupled to the fusing deuterons.

While it is not possible to retrospectively specify all the parameters that influenced the conversion of laser energy into fusion neutron energy, the experimental devices that provided both the largest and smallest yields can be characterized at least in part. Likewise, here it can be assumed that different lasers and targets were used to obtain maximum yield value in each experiment. Differences in experiments will be reflected by different values of the parameters of the above-mentioned power function $Y=QE^{\alpha}$. It is also obvious that in general a number of power functions can be fitted to experimental points shown in **Figure 1**, which differ in values of both parameters Q and α [1, 2].

Figure 2 shows a DD-neutron *Y-E* diagram, where for simplicity, only 5 lines $Y = QE^{1.65}$ are plotted, for Q ranging from 14 (Y_{SGG}) to 7.5 × 10⁶ (Y_{BL-h}). In addition, those experimental data that relate to those lines are presented. One of these experiments dealing with deuterium cluster targets irradiated with 100 fs pulses, see Ma04 label, gave the dependence



 $Y = 7.1 \times 10^4 \cdot E^{1.6}$ [1, 2]. The efficiency of this experiment given by the value of the *Q* parameter was higher by a factor of ≈ 35 than that of experiments involving the PALS experiment, which matches the solid line $Y_{BL} = 2,000 \cdot E^{-1.65}$ [3]. The PALS experiment revealed a non-linear interaction of a 350-ps pulse with plasma [36], which resulted in the production of up to 4 $\times 10^8$ DD neutrons per shot, see PALS label [20]. The analysis showed that the central-of-mass velocity of ions was much higher than their temperature: $E_i \gg kT_i$, i.e., $kT_i \approx 1$ keV, proton kinetic energy of $\approx 1-4$ MeV, and energy of deuterons reached a value of about 3 MeV [3, 37].

The last dependence Y_{BL} is associated with experiments where the self-focusing due to the interaction of laser beam with preplasma occurs spontaneously or in a controlled manner. In the case of yield labeled Pr98, a nanosecond pre-pulse was used to produce pre-plasma, which allowed a measurable neutron yield to be gained by self-focusing the main femtosecond pulse [17]. The yield labeled Be06 is a result of experimental study devoted to the effect of pre-pulses with various durations on the neutron yield in laser picosecond plasma [18]. Another experiment labeled Iz02 is the result of the effect of the pre-pulse on yield, where the pre-pulse delivered 10^{-4} of energy of the main 500 fs-pulse to the target [19]. Even in this case, the main pulse interacted with a pre-formed plasma.

The other iodine laser system, like the PALS one, producing pulses with duration of 250 ps and with total energy up to 10 kJ is the ISKRA-5 12-channel laser system [21]; see Iskra5 label in **Figure 2**. The yield reaching a value up to 5×10^9 DD-neutron per shot was produced with energy of 10 kJ delivered to the inverted-corona target, where the ion kinetic energy was converted into thermal energy at a temperature of 10–20 keV.

It is obvious that even this yield value matches the line $Y_{BL} = 2,000 \cdot E^{1.65}$.

The values of the absolute yields of DD neutrons tagged with Ω label were taken from two experimental campaigns at OMEGA. As targets where used the glass capsules 880 μ m in diameter, 2.0 μ m thick, and filled with 3.6 atm D₂ and 7.9 atm D³He gas, and with 9.3 atm of D₂ gas which were irradiated with 60 laser beams providing \approx 2.5 and \approx 5.2 kJ, respectively [22].

The highest number of 1×10^{12} DD-neutrons from an "exploding-pusher" powered by 130.6 kJ laser energy were achieved at the National Ignition Facility [23]. Most of the "exploding-pushers" tagged with NIF-DD label follow the power law dependence on laser energy, $Y_{BL} = 2,000 \cdot E^{-1.65}$, well, as **Figure 2** shows.

Important experimental results marked with V1, V2, and V3 labels were obtained using the Vulcan laser system [25–27]. These experiments using 0.9-1.2 ps laser pulses have shown that the neutron yield can decrease with increasing laser energy. In the case of the V3 experiment, there could be such conditions under which the interaction of the main laser pulse with the pre-plasma could initiate different processes that consume laser energy at the expense of acceleration of deuterons and, thus, neutron yield. The pre-plasma was produced by a pre-pulse of the main 400 J laser pulse irradiating the target with a peak focused intensity of 4 \times 10^{20} Wcm⁻² at a contrast ratio of $\sim 5 \times 10^{-8}$ [27]. A higher yield was observed when a lower laser energy of 90 J was focused on the target with the peak laser intensity of 5 \times 10 19 W/cm 2 at a contrast ratio of 10^{-7} [26]. The highest yield was achieved with low energy of 20 J and intensity of 10^{19} W/cm² [25]. In this case, it can be assumed that no pre-plasma was produced due to the low contrast ratio. The value of this neutron yield of 7×10^7

neutrons/sr, see V1 label, is higher by a factor of ≈ 12 than that obtained with the pulse energy of 400 J [25, 27]. In the latter case, it can be assumed that the pre-plasma probably plays an insignificant role.

Figure 2 also shows that measured scaling of fusion yield as a function of laser energy may differ from $Q E^{1.65}$ in individual experiments. Although the Sy06 data presented by four types of asterisks (\bigstar - \bigstar) were scaled by a power law with exponent varying from 2 to 2.2 in [1, 2, 10] and quadratic dependency was used to analyse them using hydrodynamic scaling and other methods [11, 24], it is clear that inserting them into the metadiagram shown in Figure 2 supports the overall trend of energy dependency represented by the $Y=Q E^{1.65}$ relationship. Using this dependency also allows us to approximately quantify the effectiveness of other experiments in the frame of the metadiagram, for example the SGII-Up experiment, as already stated in [12]. This experiment was devoted to the plasma compression with the use of eight laser beams that delivered 12-kJ energy in 2 ns on a CD₂ flat target at the ShenGuang-II Upgrade (SGII-Up) facility. As stated in [12], the highest yield of about $1 \times$ 10⁸ neutrons achieved at 12-kJ energy is in good agreement with the yield observed at 600-J energy delivered in 350 ps on a CD₂ flat target at the PALS facility. The yield values obtained in the GXII95 and SGIII15 cryogenic experiments also match the Y_{SGG} line [29, 30]. The metadiagram also shows other experimentally observed yields of DD-neutrons which were produced with higher as well as lower efficiency in comparison with our basic power law dependence on laser energy $Y_{BL} = 2,000 \cdot E^{1.65}$. The efficiency of production of 1×10^{12} DD neutrons with 35 kJ laser energy delivered by the OMEGA laser system is higher by a factor of ≈ 16 than the basic one with Q = 2,000, see $\Omega 96$ label [9].

Summarizing the laser-fusion experiments, the highest laser fusion yields by cryogenic targets were 1.9×10^{16} neutrons from deuterium-tritium (DT) implosions driven with 1.5 MJ laser pulses [38], as Figure 3 shows. We note that the values of the DT-neutron yield shown in Figure 3 are presented without a correction taking into account differences in DD and DT fusion reaction cross sections, although in the case of a thermonuclear reaction at a certain temperature, the fusion probability of the deuterium-tritium reaction is nearly by a factor of 100 larger than that of the deuterium-deuterium reaction [29]. If this factor is taken into account, then the values of DT-neutron yields achieved at the OMEGA and NIF experiments (tagged with 11–15 labels) are shifted to the Y_{BL} line that determine the results of standard DD-fusion experiments. Figure 3 shows only a few experimental results concerning the DT-neutron yields. It may be noted that, for example, other values reported by R. S. Craxton et al. [48] are located between points 2-5 and 10-11.

The configuration of the experimental points in the *Y*-*E* diagram shows relationships and connections between experiments of completely different levels that can be hardly to be expected. It is obvious that the empirical yield dependence on laser energy, $Y = QE^{1.65}$, is the simplest dependency that can be used to characterize experimental values obtained for an energy range exceeding 9 orders of magnitude. It is also a fact that when the fusion experiments described above were conducted with the use of high-quality laser pulses with a sufficiently high contrast



ratio, fusion gains at a given laser energy increased by more than four orders of magnitude [25]. The use of the power law dependence on laser energy reduces all processes that determine the conversion of laser energy to the production and acceleration of fusion ions to only two parameters Q and α . For a given energy, the Q coefficient allows comparing the efficiency of different laser systems, which is given by the number of neutrons per joule of laser energy. For a given parameter Q, the $\alpha = 1.65$ coefficient indicates the non-linearity dependence of yield on laser energy delivered to the target within the entire experimental point configuration. Regardless of low or very high laser intensities, "cleaner" experiments are needed to elucidate other values of α that have been observed in some experiments [1, 2].

DD AND p¹¹B FUSION EXPERIMENT AT PALS

The Prague Asterix Laser System (PALS) in Prague was used not only for the DD fusion experiments [3, 20] but also as a driver for the fusion reactions of hydrogen protons with the boron isotope ¹¹B releasing three alpha particles and energy of 8.7 MeV: $p + {}^{11}B = 3\alpha + 8.7 MeV$ [6, 43, 44]. First, A. Picciotto et al. obtained a high number of α particles (10⁹ α /sr/shot) released from the plasma which was produced on a silicone target, doped by boron and enriched with hydrogen by an annealing process. The target was exposed to laser intensity of 3×10^{16} W/cm² (500-J energy in 0.3 ns (full-width at half-maximum, FWHM) [49]. Very high yield, well-above $10^{10} \alpha$ /sr/shot, was obtained by L. Giuffrida et al. [6] when a 0.5-mm thick boron nitride targets were irradiated with 0.3 ns pulses delivering energy of

TABLE 1 Yield of $p + {}^{11}B \rightarrow$	3α + 8.7MeV and D + D \rightarrow ³ He (0.82 MeV) + n
(2.45 MeV) fusion reactions per	formed at the PALS facility.

Laser energy	Target	Yield/steradian /shot	Fusion product	References
500 J	hydrogenated Si target doped by ¹¹ B	10 ⁹	3α particles + 8.7 MeV	[49]
600 J	0.5-mm boron nitride	6.5×10^{10}	3α particles + 8.7 MeV	[6]
600 J	0.2–0.5 mm CD ₂	3.2×10^{7}	2.45 MeV neutrons	[3, 20]

Laser pulse duration of 0.3 ns (FWHM), wavelength of 1,315 nm, focal spot diameter of 70 μ m.

600 J. It has been shown that this yield of α particles is not thermonuclear in nature, but rather results from a beam-driven fusion process.

Table 1 shows the yields of α particles and DD neutrons released from the fusion plasma produced by the PALS laser. The first two rows show an increase in the number of α particles due to a change in the composition of the target. The number of α particles emitted per steradian and laser shot is three orders of magnitude higher than the number of DD neutrons produced with the same laser intensity and energy. If we consider the possibility of increasing yield by using a high-quality laser, as mentioned above, then the use of picosecond or shorter duration CPA- laser pulses that do not produce pre-plasma but initiate non-thermal fusion reactions in p¹¹B plasma could help solve a key problem for controlled nuclear fusion energy generation [50, 51].

CONCLUSIONS

In this work, we restricted our study on the scaling law of fusion yields, $Y = QE^{1.65}$, derived empirically from the available experimental data. The performed analysis showed that this function fits the largest number of experimental data on the energy scale covering 9 orders of magnitude, namely for the line with Q = 2,000. Published experimental data made it possible to classify individual experiments within a metadiagram

REFERENCES

- Madison KW, Patel PK, Price D, Edens A, Allen M, Cowan TE, et al. Fusion neutron and ion emission from deuterium and deuterated methane cluster plasmas. *Phys Plasmas*. (2004) 11:270–7. doi: 10.1063/1.1632906
- Madison KW, Patel PK, Allen M, Price D, Fitzpatrick R, Ditmire T. Role of laser-pulse duration in the neutron yield of deuterium cluster targets. *Phys Rev A*. (2004) **70**:053201. doi: 10.1103/PhysRevA.70.053201
- Krása J, Klír D, Velyhan A, Margarone D, Krouský E, Jungwirth K, et al. Observation of repetitive bursts in emission of fast ions and neutrons in sub-nanosecond laser-solid experiments. *Laser Part Beams*. (2013) 31:395– 401. doi: 10.1017/S0263034613000360
- Hurricane OA, Springer PT, Patel PK, Callahan DA, Baker K, Casey DT, et al. Approaching a burning plasma on the NIF. *Phys Plasmas*. (2019) 26:052704. doi: 10.1063/1.5087256

in such a way that the number of fusion reactions increases with increasing energy as $E^{1.65}$ at the same value of the Q coefficient. This coefficient summarizes the effect of all possible processes taking place during laser-target interaction on fusion neutron production. Then the part of *E* that is not converted into energy carried by fusion neutrons can be quantified by 1/Q. In this case, the experiments tagged with $Y_{\rm fs}$ label are \approx 200 times more productive than the $Y_{\rm BL}$ experiments and the V1 experiment is then even \approx 3,700 times more productive than the Y_{BL} ones. The Y_{SGG} experimental configurations, on the other hand, are 25 times less productive than the $Y_{\rm BL}$ ones. It is obvious that in order to search for optimal conditions of a generation of fusion neutrons using some kind of laser system, it is appropriate to compare the observed Y = Q Y(E) dependence with the experimental results of other experiments using metadiagram. The values of the Q coefficient offer the possibility of finding the effective acceleration of ions and the production of fusion neutrons and one can assume that they will also be valid in the case of proton boron fusion.

It goes without saying that every laser system used for a production of fusion neutrons has its own specifics that can be explained by many different sub-processes, as shown by many key works. However, the method presented allows each interaction laser system to be placed in the overall context of the lasermatter interaction.

DATA AVAILABILITY STATEMENT

The raw data supporting the conclusions of this article will be made available by the authors, without undue reservation.

AUTHOR CONTRIBUTIONS

JK: wrote the manuscript. DK: reviewed the manuscript and collected experimental data. All authors contributed to the article and approved the submitted version.

FUNDING

The research leading to these results has received funding from the Czech Science Foundation (Grant No. 19-02545S).

- Azechi H. A pathway to laser fusion energy in Japan. J Phys Conf Ser. (2016) 717:012119. doi: 10.1088/1742-6596/717/1/012119
- Giuffrida L, Belloni F, Margarone D, Petringa G, Milluzzo G, Scuderi V, et al. High-current stream of energetic α particles from laser-driven protonboron fusion. *Phys Rev E.* (2020) **101**:013204. doi: 10.1103/PhysRevE.101. 013204
- Ping Y, Smalyuk VA, Amendt P, Tommasini R, Field JE, Khan S, et al. Enhanced energy coupling for indirectly driven inertial confinement fusion. *Nat Phys.* (2019) 15:138–41. doi: 10.1038/s41567-018-0331-5
- Nakai S. Power photonics for green earth –strategic approach to the better life. EPJ Web Conf. (2013) 59:01001 doi: 10.1051/epjconf/20135901001
- Alvarez J, Fernández-Tobia J, Mima K, Nakai S, Kar S, Kato Y, et al. Laser driven neutron sources: characteristics, applications and prospects. *Phys Proc.* (2014) 60:29–38. doi: 10.1016/j.phpro.2014.11.006

- 10. Symes D, Hartke R, Buergens F, Ditmire T, Patel P, Price D. Annual Progress Report The Texas Center for High Intensity Laser Science and the Texas Petawatt Project. (2006). p. 47.
- Kimura S, Bonasera A. Hydrodynamic scaling analysis of nuclear fusion driven by ultra-intense laser-plasma interactions. *Int J Modern Phys E.* (2012) 21:1250102. doi: 10.1142/S0218301312501029
- Zhang G, Huang M, Bonasera A, Ma YG, Shen BF, Wang HW, et al. Nuclear probes of an out-of-equilibrium plasma at the highest compression. *Phys Lett* A. (2019) 383:2285–9. doi: 10.1016/j.physleta.2019.04.048
- Volkov RV, Golishnikov DM, Gordienko VM, Mikheev PM, Savel'ev AB, Sevast'yanov VD, et al. Neutron generation in dense femtosecond laser plasma of a structured solid target. *JETP Lett.* (2000) 72:401–4. doi: 10.1134/1.1335116
- Soures J M, McCrory R L, Verdon CP, Babushkin A, Bahr RE, Boehly TR, et al. Direct-drive laser-fusion experiments with the OMEGA, 60beam, >40 kJ, ultraviolet laser system. *Phys Plasmas.* (1996) 3:2108– 12. doi: 10.1063/1.871662
- Krása J, Králík M, Velyhan A, Šolc J, Juha L, Scholz M, et al. Anisotropy of the emission of DD-fusion neutrons caused by the plasma-focus vessel. *Plasma Phys Control Fusion*. (2008) **50**:125006. doi: 10.1088/0741-3335/50/12/125006
- Králík M, Krása J, Velyhan A, Scholz M, Ivanova-Stanik IM, Bienkowska B, et al. Application of a bonner sphere spectrometer for determination of the energy spectra of neutrons generated by ≈1 MJ plasma focus. *Rev Sci Instrum.* (2010) 81:113503. doi: 10.1063/1.3488372
- Pretzler G, Saemann A, Pukhov A, Rudolph D, Schätz T, Schramm U, et al. Neutron production by 200 mJ ultrashort laser pulses. *Phys Rev E.* (1998) 58:1165–8. doi: 10.1103/PhysRevE.58.1165
- Belyaev VS, Vinogradov VI, Matafonov AP, Krainov VP, Lisitsa VS, Andrianov VP, et al. Effect of prepulses with various durations on the neutron yield in laser picosecond plasma. *Laser Phys.* (2006) 16:1647– 57. doi: 10.1134/S1054660X06120097
- Izumi N, Sentoku Y, Habara H, Takahashi K, Ohtani F, Sonomoto T, et al. Observation of neutron spectrum produced by fast deuterons via ultraintense laser plasma interactions. *Phys Rev E.* (2002) 65:036413. doi: 10.1103/PhysRevE.65.036413
- Klir D, Krasa J, Cikhardt J, Dudzak R, Krousky E, Pfeifer M, et al. Efficient neutron production from sub-nanosecond laser pulse accelerating deuterons on target front side. *Phys Plasmas*. (2015) 22:093117. doi: 10.1063/1.4931460
- Bessarab AV, Gaidash VA, Dolgoleva GV, Zhidkov NV, Izgorodin VM, Kirillov GA, et al. Results of first experiments with fusion targets at the Iskra-5 high-power laser installation. *Sov Phys JETP*. (1992) 75:970–3.
- Waugh CJ, Rosenberg MJ, Zylstra AB, Frenje JA, Séguin FH, Petrasso RD, et al. A method for in situ absolute DD yield calibration of neutron time-of-flight detectors on OMEGA using CR-39-based proton detectors. *Rev Sci Instrum.* (2015) 86:053506. doi: 10.1063/1.4919290
- Rosenberg MJ, Zylstra AB, Seguin FH, Rinderknecht HG, Frenje JA, Gatu Johnson M, et al. Investigation of ion kinetic effects in directdrive exploding-pusher implosions at the NIF. *Phys Plasmas*. (2014) 21:122712. doi: 10.1063/1.4905064
- 24. Barbui M, Bang W, Bonasera A, Hagel K, Schmidt K, Natowitz JB, et al. Measurement of the plasma astrophysical S factor for the ³He(d, p)⁴He reaction in exploding molecular clusters. *Phys Rev Lett.* (2013) 111:082502. doi: 10.1103/PhysRevLett.111.082502
- 25. Norreys PA, Fews AP, Beg FN, Bell AR, Dangor AE, Lee P, et al. Neutron production from picosecond laser irradiation of deuterated targets at intensities of 10₁₉ W cm⁻². *Plasma Phys Control Fusion.* (1998) 40:175–82. doi: 10.1088/0741-3335/40/2/001
- Habara H, Lancaster KL, Karsch S, Murphy CD, Norreys PA, Evans RG, et al. Ion acceleration from the shock front induced by hole boring in ultraintense laser-plasma interactions. *Phys Rev E.* (2004) 70:046414. doi: 10.1103/PhysRevE.70.046414
- Norreys PA. Lancaster KL, Habara H, Davies JR, Mendonc JT, Clarke RJ, et al. Observation of ion temperatures exceeding background electron temperatures in petawatt laser-solid experiments. *Plasma Phys Control Fusion*. (2005) 47:L49–56. doi: 10.1088/0741-3335/47/11/L01
- Fritzler S, Najmudin Z, Malka V, Krushelnick K, Marle C, Walton B, et al. Ion heating and thermonuclear neutron production from high-intensity subpicosecond laser pulses interacting with underdense plasmas. *Phys Rev Lett.* (2002) 89:165004. doi: 10.1103/PhysRevLett.89.165004

- Daido H, Yamanaka M, Mima K, Nishihara K, Nakai S., Kitagawa Y, et al. Neutron production from a shell-confined carbon-deuterium plasma by 1.06 μm laser irradiation. *Appl Phys Lett.* (1987) 51:2195–6. doi: 10.1063/1.98937
- Pu Y, Huang T, Lei H, Li P, Zhang X, Zheng J, et al. Direct-drive cryogenictarget implosion experiments on SGIII prototype laser facility. *Phys Plasmas*. (2015) 22:042704. doi: 10.1063/1.4917329
- Harding DR, Sangster TC, Meyerhofer DD, McKenty PW, Lund LD, Elasky L, et al. Producing cryogenic deuterium targets for experiments on OMEGA. *Fusion Sci Tech*. (2005) 48:1299–306. doi: 10.13182/FST05-A1079
- Tanaka KA, Yamanaka T, Nishihara K, Norimatsu T, Miyanaga N, Shiraga H, et al. Cryogenic deuterium target experiments with the GEKKO XII, green laser system. *Phys Plasmas*. (1995) 2:2495–503. doi: 10.1063/1.871211
- Zulick C, Dollar F, Chvykov V, Davis J, Kalinchenko G, Maksimchuk A, et al. Energetic neutron beams generated from femtosecond laser plasma interactions. *Appl Phys Lett.* (2013) 102:124101. doi: 10.1063/1. 4795723
- Disdier L, Garçonnet J-P, Malka G, Miquel J-L. Fast neutron emission from a high-energy ion beam produced by a high-intensity subpicosecond laser pulse. *Phys Rev Lett.* (1999) 82:1454. doi: 10.1103/PhysRevLett. 82.1454
- Ditmire T, Zweiback J, Yanovsky VP, Cowan TE, Hays G, Wharton KB. Nuclear fusion in gases of deuterium clusters heated with a femtosecond laser. *Phys Plasmas.* (2000) 7:1993. doi: 10.1063/1.874020
- Krása J, Klír D, Rezáč K, Cikhardt J, Krus M, Velyhan A, et al., Production of relativistic electrons, MeV deuterons and protons by sub-nanosecond terawatt laser. *Phys Plasmas*. (2018) 25:113112. doi: 10.1063/1.5052146
- Krása J, Jungwirth K, Krouský E, Láska L, Rohlena K, Pfeifer M, et al. Temperature and centre-of-mass energy of ions emitted by laserproduced polyethylene plasma. *Plasma Phys Control Fusion*. (2007) 49:1649– 59. doi: 10.1088/0741-3335/49/10/004
- Le Pape S, Berzak Hopkins LF, Divol L, Pak A, Dewald EL, Bhandarkar S, et al. Fusion energy output greater than the kinetic energy of an imploding shell at the national ignition facility. *Phys Rev Let.* (2018) 120:245003. doi: 10.1103/PhysRevLett.120.245003
- Campbell EM, Mead WC. 10x Liquid Density Target Experiments, in Laser Program Annual Report 1978: Vol. 2. Lawrence Livermore National Laboratory (1980). p. 6–52.
- Peng HS, Zheng ZJ, Zhang BH, Ding YK, Tang YJ, Zheng YM, et al. Directdrive implosion experiments on the SG-II laser facility. J Fusion Energy. (2000) 19:81–85. doi: 10.1023/A:1012233910891
- 41. Yamanaka C, Azechi H, Fujiwara E, Ido S, Izawa Y, Jitsuno T, et al. Cannonball Target Experiment With the GEKKO Laser System at ILE Osaka, in Research Report (1984-1986), Institute of Laser Engineering, Osaka University, p. 179.
- Iguchi T, Shimizu Y, Takada E, Nakazawa M, Miyanaga N, Yamanaka M, et al. D-T neutron measurements on GEKKO XII laser inertial fusion plasmas by multiactivation foil method. *Nucl Sci Technol.* (1988) 25:548– 51. doi: 10.1080/18811248.1988.9733628
- Miyanaga N, Chen Y-W, Unemoto M, Yamanaka M, Yamanaka T, Nakai S, et al. Neutron penumbral imaging at Gekko XII (abstract). *Rev Sci Instrum.* (1990) 61:3230. doi: 10.1063/1.1141645
- 44. Yamanaka C, Nakai S, Yabe T, Nishimura H, Uchida S, Izawa Y, et al. Laser implosion of high-aspect ratio targets produces thermonuclear neutron yields exceeding 1012 by use of shock multiplexing. In: *Research Report*. Institute of Laser Engineering, Osaka University. (1984-1986). p. 215.
- 45. NIF Liquid-Hydrogen Target Gets its First Test; in Experimental Highlights. Lawrence Livermore National Laboratory (2016).
- Hurricane OA, Callahan DA, Casey DT, Celliers PM, Cerjan C, Dewald EL, et al. Fuel gain exceeding unity in an inertially confined fusion implosion. *Nature*. (2014) 506:343–8. doi: 10.1038/nature13008
- Park H-S, Hurricane OA, Callahan DA, Casey DT, Dewald EL, Dittrich TR, et al. High-adiabat high-foot inertial confinement fusion implosion experiments on the national ignition facility. *Phys Rev Lett.* (2014) 112:055001. doi: 10.1103/PhysRevLett.112.055001
- Craxton RS, Anderson KS, Boehly TR, Goncharov VN, Harding DR, Knauer JP, et al. Direct-drive inertial confinement fusion: a review. *Phys Plasmas*. (2015) 22:110501. doi: 10.1063/1.4934714

- Picciotto A, Margarone D, Velyhan A, Bellutti P, Krasa J, Szydlowsky A, et al. Boron-proton nuclear-fusion enhancement induced in borondoped silicon targets by low-contrast pulsed laser. *Phys Rev X.* (2014) 4:031030. doi: 10.1103/PhysRevX.4.031030
- Hora H. Difference between relativistic petawatt-picosecond laser-plasma interaction and subrelativistic plasma-block generation. *Laser Part Beams*. (2005) 23:441–451. doi: 10.1017/S0263034605050627
- Hora H, Miley GH, Eliezer S, Nissim N. Pressure of picosecond CPA laser pulses substitute ultrahigh thermal pressures to ignite fusion. *High Energy Density Phy.* (2020) 35:100739. doi: 10.1016/j.hedp.2019.100739

Conflict of Interest: The authors declare that the research was conducted in the absence of any commercial or financial relationships that could be construed as a potential conflict of interest.

Copyright © 2020 Krása and Klír. This is an open-access article distributed under the terms of the Creative Commons Attribution License (CC BY). The use, distribution or reproduction in other forums is permitted, provided the original author(s) and the copyright owner(s) are credited and that the original publication in this journal is cited, in accordance with accepted academic practice. No use, distribution or reproduction is permitted which does not comply with these terms.