



## OPEN ACCESS

EDITED AND REVIEWED BY  
Auroop Ratan Ganguly,  
Northeastern University, United States

\*CORRESPONDENCE  
Daniel Jato-Espino  
✉ djato@universidadviu.com

SPECIALTY SECTION  
This article was submitted to  
Water and Built Environment,  
a section of the journal  
Frontiers in Water

RECEIVED 07 December 2022  
ACCEPTED 28 December 2022  
PUBLISHED 06 January 2023

CITATION  
Jato-Espino D, Charlesworth S,  
Leitão JP and Rodríguez Sánchez JP  
(2023) Editorial: Urban drainage in a  
context of climate and land cover  
changes. *Front. Water* 4:1118338.  
doi: 10.3389/frwa.2022.1118338

COPYRIGHT  
© 2023 Jato-Espino, Charlesworth,  
Leitão and Rodríguez Sánchez. This is  
an open-access article distributed  
under the terms of the [Creative  
Commons Attribution License \(CC BY\)](https://creativecommons.org/licenses/by/4.0/).  
The use, distribution or reproduction  
in other forums is permitted, provided  
the original author(s) and the copyright  
owner(s) are credited and that the  
original publication in this journal is  
cited, in accordance with accepted  
academic practice. No use, distribution  
or reproduction is permitted which  
does not comply with these terms.

# Editorial: Urban drainage in a context of climate and land cover changes

Daniel Jato-Espino<sup>1\*</sup>, Susanne Charlesworth<sup>2</sup>, João P. Leitão<sup>3</sup>  
and Juan Pablo Rodríguez Sánchez<sup>4</sup>

<sup>1</sup>GREENIUS Research Group, Universidad Internacional de Valencia - VIU, Valencia, Spain, <sup>2</sup>Centre for Agroecology, Water Resilience, Coventry University, Coventry, United Kingdom, <sup>3</sup>Department of Urban Water Management, Eawag-Swiss Federal Institute of Aquatic Science and Technology, Dübendorf, Switzerland, <sup>4</sup>Environmental Engineering Research Center (CIIA), Department of Civil and Environmental Engineering, Universidad de los Andes, Bogota, Colombia

## KEYWORDS

land cover change (LCC), urban drainage, Green Infrastructure (GI), climate change, Sustainable Drainage Systems (SuDS)

## Editorial on the Research Topic

## Urban drainage in a context of climate and land cover changes

Traditional drainage systems rely on networks of interconnected pipes and manholes to collect and quickly transport runoff to an outlet where it is discharged into bodies of water. This approach to runoff management is proving to be insufficient to manage the impacts of land cover and climate change (Russo et al., 2021). Increasing sealing from urban development causes high runoff volumes and speeds, which is combined with the existence of more intense and frequent storm events due to changing climate (Jato-Espino et al., 2019). Ultimately, these effects favor the occurrence of flooding and diffuse pollution phenomena. Adapting urban planning to these changes is essential to ensure the hydrological sustainability of the cities of the future (Marhaento et al., 2018).

Despite efforts by the scientific community to better manage stormwater in cities, there are still research gaps that need to be filled to provide insight into mitigating the impacts of land cover and climate change on urban drainage. Such is the case in the assessment of Combined Sewer Overflows (CSOs) with a focus on the potential of Green Infrastructure (GI) and Sustainable Drainage Systems (SuDS) for water retention at source. Another area that needs further study is the implementation of resilient drainage practices in public policies. This Research Topic aims to produce knowledge on these matters, emphasizing the role of GI and SuDS to cope with increasing hydrological stress caused by land cover and climate change. This collection contains three original research papers and one research report that are overviewed below.

Förster et al. performed a series of artificial precipitation experiments to simulate the decrease in runoff coefficient caused by green roofs when the flow length and slope in the substrate layer were varied. The consideration of flow lengths under 5 m and non-pitched roofs is new and gives insight into the potential of green roofs to minimize stormwater flooding in cities. Using Hanover (Germany) as a case study, the authors found that minimizing the slope and maximizing the flow length reduced the runoff coefficient from

30% to <10% for a return period of 100 years. These figures were confirmed numerically using the Catchment Modeling Framework (CMF). These results represent a paradigm shift in green roof design and provide practical information that can help update current guidelines and standards.

Roseboro et al. used the Storm Water Management Model (SWMM) to gain understanding of the performance of permeable pavements to attenuate CSOs favored by climate change impacts in the city of Buffalo (USA). The results of the simulations showed that the CSO volumes under the most critical Representative Concentration Pathways (RCP 8.5) can increase in the range of 11 to 73% depending on the duration of precipitation and the considered return periods. Permeable pavements have a reduction potential of 2 to 31% of such CSO volumes and are particularly effective in storm events with short return periods and short precipitation durations. These results are of great interest to facilitate the strategic rehabilitation of urban surfaces through permeable pavements, which are the easiest type of SuDS to implement in cities.

Muhandes et al. developed a computational model (CityWatStorm) to assess the role of SuDS in reducing CSOs and flood volume. When compared to the results of InfoWorks ICM model using Norwich (UK) as a case study, CityWatStorm was found to capture the benefits of SuDS with an accuracy of 95%, while CSOs and flood volumes were estimated with an accuracy between 78 and 83%. Furthermore, the proposed tool was developed to overcome some limitations in existing software such as speed in optimization or uncertainty analysis in long-term simulations. Therefore, CityWatStorm can be useful for both companies and administrations to develop drainage plans and conduct long-term assessments of large catchment areas.

Galarza-Molina et al. conducted a literature review to examine the incorporation of resilience in urban drainage systems into public policies worldwide. The knowledge gained in this way was validated in a workshop with experts and then used for recommendations at the city level in Colombia. Tools and concepts such as the urban water transition framework and the hydro-social contract were highlighted as means to facilitate the transition to sustainable cities in terms of water management. In addition, technical panels, focus groups, workshops, and information sessions with the citizenry were identified as key aspects to facilitate the generation of ideas. Regarding

information, the authors also emphasize the importance of using tools to visualize the state of urban drainage in order to facilitate the implementation of solutions for its improvement.

The findings of these investigations help provide insights into the importance of exploring alternative drainage approaches to address land cover and climate change. The results of the contributions in this Research Topic rotate from technical questions to decision-making, thus helping to improve the understanding of the benefits of sustainable stormwater management at different levels.

## Author contributions

DJ-E, SC, and JR reviewed the articles in the Research Topic. DJ-E, SC, JL, and JR co-edited the Research Topic and analyzed how the articles fit within. All authors contributed to the article and approved the submitted version.

## Funding

The development of this Research Topic was supported by the Conselleria for Innovation, Universities, Science and Digital Society of the Generalitat Valenciana, grant number CIGE/2021/079.

## Conflict of interest

The authors declare that the research was conducted in the absence of any commercial or financial relationships that could be construed as a potential conflict of interest.

## Publisher's note

All claims expressed in this article are solely those of the authors and do not necessarily represent those of their affiliated organizations, or those of the publisher, the editors and the reviewers. Any product that may be evaluated in this article, or claim that may be made by its manufacturer, is not guaranteed or endorsed by the publisher.

## References

- Jato-Espino, D., Lobo, A., and Ascorbe-Salcedo, A. (2019). Urban flood risk mapping using an optimised additive weighting methodology based on open data. *J. Flood Risk Manage.* 12, e12533. doi: 10.1111/jfr3.12533
- Marhaento, H., Booij, M. J., and Hoekstra, A. Y. (2018). Hydrological response to future land-use change and climate change in a tropical

catchment. *Hydrol. Sci. J.* 63, 1368–1385. doi: 10.1080/02626667.2018.1511054

Russo, B., Valentín, M. G., and Tellez-Álvarez, J. (2021). The relevance of grated inlets within surface drainage systems in the field of urban flood resilience. A review of several experimental and numerical simulation approaches. *Sustainability* 13, 7189. doi: 10.3390/su13137189